

MODEL No. 12T- SERIES COPPER "C" CONNECTOR DIES

Die sets are for Copper "C" Connectors which are "C" shaped copper sections for terminating main and tap copper conductors. Our dies are made to the same specifications as Burndy, Cabac and Dulmison/PLP (Preformed Line Products). We also supply a range of Utilux die sets for copper conductor terminations.

Model No.	Description	Equivalent to		
	Description	Burndy	Cabac	Dulmison/PLP
12T-U1011	Compression Die C-Connector	U1011	HT130-C1011	-
12T-U997	Compression Die C-Connector	U997	HT130-C997	-
12T-UC	Compression Die C-Connector	UC	HT130-CC	-
12T-UO	Compression Die C-Connector	UO	HT130-CO	DU1315
12T-DU1315	Compression Die C-Connector	UO	HT130-CO	DU1315

"AUSTRALIAN MADE"

Cutting dies manufactured in Australia from high tensile steel billets and heat treated to maximise strength and durability.









12T-U1011

12T-U997

DIES FOR "YGHC" STYLE EARTHING CONNECTORS

Model No.	To suit Burndy earthing	COPPER CONDUCTOR RANGE		IMAGE
(12Tonne)	connector, catalogue no.	TAP mm ²	RUN mm²	
12T-UC	YGHC2C2	10~35	10~35	
12T-U0	YGHC26C2	50~70	16~35	
12T-UO	YGHC26C26	50~70	50~70	
12T-U997	YGHC29C26	95~150	16~70	
12T-U997	YGHC29C29	95~150	95~120	
12T-U1011	YGHC34C26	150~240	10~70	
12T-U1011	YGHC34C29	150~240	95~120	
12T-U1011	YGHC34C34	150~240	150~240	

DIES FOR "YGHR" STYLE EARTHING CONNECTORS

Model No.	To suit Burndy earthing connector, catalogue no.	COPPER CONDUCTOR RANGE		IMAGE
(12Tonne)		TAP mm²	RUN mm ²	
12T-UC	YGHR26C12	10~35	10~35	
12T-UO	YGHR26C58	50~70	16~35	
12T-UO	YGHR26C34	50~70	50~70	
12T-U997	YGHR26C100	95~150	16~35	
12T-U997	YGHR29C12	95~150	50~70	
12T-U997	YGHR29C58	95~150	95~150	

DIES FOR "YGHP" STYLE EARTHING CONNECTORS

Model No.	To suit Burndy earthing	COPPER CONDUCTOR RANGE		IMAGE
(12Tonne)	connector, catalogue no.	TAP mm ²	RUN mm²	
12T-UO	YGHP2C2	10~35	10~35	
12T-U997	YGHP29C26	15~120 (13-15mm ROD)	50~70	
12T-U997	YGHP29C29		95~120	
12T-U997	YGHP34C26	150~240 (16-19mm ROD)	50~70	
12T-U997	YGHP34C29		95~120	
12T-U1011	YGHP34C34		150~240	