



**ABI 1**

**NEW** *intercable*

Outer jacket cutter with spring quick release system

**PRECISION**

Cutting depth adjustable up to 3mm, thus no damage to the underlying layers of the cable

**VERSATILE**

Setting of round, longitudinal and spiral cuts

**EFFICIENCY**

Blade suitable for all types of cable insulation

**PROTECTION**

The blocking system prevents opening in the position: longitudinal cut. This prevents the blade from breaking off due to misuse

**HANDLING**

No tilting due to axial pulling of the tool in the longitudinal direction

**SAFETY**

The innovative design ensures an injury-free working

**ERGONOMICS**

The optimally adapted shape of the tool enables fatigue-free working



# Technical description

- Wide range of applications: diameter 4.5 mm to 29 mm
- Suitable for soft and hard insulation types of cables
- Hardened steel blade
- Special grinding of the blade for clean removal of the outer casing
- Round, longitudinal and spiral cuts possible
- No tilting due to axial pulling of the device in the longitudinal direction
- Cutting depth in increments of 0.1mm to 3mm adjustable using the rotary knob (clockwise)
- No damage to the underlying layers
- Thanks to the special sliding properties of the contact surface, resistance-free working on the cable is guaranteed
- Small and compact design
- Handy & ergonomic design
- Blocking system: This function prevents opening in the position: longitudinal cut. This prevents the blade from breaking off due to misuse.

Attention: Not suitable for work under voltage

Description	Order No.	Dimensions	Weight
Outer jacket cutter with spring quick release system	ABI1	140 mm	150 g



## Use for round / spiral cuts



Unlock the cable stripper by turning the adjusting ring to the round-cut symbol (⊙)



Tension the tool to the cable using spring force



Regulate the cutting depth by turning the adjustment knob (clockwise)



Place the tool on the marking of the stripping length and make the round cut



Shift the adjusting ring to the spiral-cut symbol (⊙) to fulfil the working process

*intercable*

## Use in longitudinal cutting

For the longitudinal section, switch the adjusting ring to the longitudinal section symbol (→) and pull the device axially in the longitudinal direction



**specialisedforce.com.au**

### **SYDNEY HEAD OFFICE**

131 WOIDS AVENUE  
CARLTON NSW 2218  
TEL: (02) 9547 1844  
FAX: (02) 9547 2236  
sales@specialisedforce.com.au

### **Adelaide**

316 SOUTH ROAD  
RICHMOND SA 5033  
TEL: (08) 8352 8866  
FAX: (08) 8352 7257  
sasales@specialisedforce.com.au

### **Brisbane**

2/68 NORTHLINK PLACE  
NORTHGATE QLD 4013  
TEL: (07) 3256 6011  
FAX: (07) 3256 6055  
qldsales@specialisedforce.com.au

### **Townsville**

2/1 CIVIL ROAD  
GARbutt QLD 4814  
TEL: (07) 4728 8756  
FAX: (07) 4725 4380  
nqsales@specialisedforce.com.au

### **Melbourne**

2/18 SOUTHFORK DRIVE  
KILSYTH VIC 3137  
TEL: (03) 9761 4199  
FAX: (03) 9761 4966  
vicsales@specialisedforce.com.au

### **Perth**

19 AUGUSTA STREET  
WILLETTON WA 6155  
TEL: (08) 9354 8544  
FAX: (08) 9354 8360  
wasales@specialisedforce.com.au

### **Port Hedland**

4/13 CAJARINA ROAD  
WEDGEFIELD WA 6721  
TEL: (08) 9172 1113  
FAX: (08) 9354 9360  
pnsales@specialisedforce.com.au

### **Darwin**

4/17 WILLES ROAD  
BERRIMAH NT 0828  
TEL: (08) 8984 4453  
FAX: (08) 8984 4390  
ntsales@specialisedforce.com.au

### **Hobart**

22/370-380 CAMBRIDGE ROAD  
MORNINGTON TAS 7018  
TEL: 0427 423 217  
FAX: (03) 9761 4966  
tassales@specialisedforce.com.au