

## MODEL No. SP-40A



**INCLUDED ITEMS**  
Cutter & Carry Bag

### SPECIFICATIONS

Output Force (kN)	76
Maximum Input Pressure (bar)	700
Oil Volume Required (cc)	48
Size (mm)	340 (L)
Weight (kg)	4.0

### FEATURES

The SP-40A hydraulic cutter head cuts steel materials as well as cables up to 41mmOD and features fast cutting action with remote operation.

It can be operated by any hydraulic pump with rated oil pressure of 700 Bar. Blades are easily replaceable and have a lock pin type cutter head.

### DETAILS

Cutting of piano wire is prohibited.

Cutting Capacity	
Material	mmOD
Wire rope 6 x 7	22
Wire rope 6 x 12	25
Wire rope 6 x 19	25
Soft steel bar	20
Rebar (400 to 500Mpa)	16
Rebar (650Mpa)	12.4
Cu strands	41
Al strands	41
ACSR	38
Guy wire 1 x 7	15
Guy wire 1 x 19	20

## MODEL No. SP-55A



**INCLUDED ITEMS**  
Cutter & Carry Bag

### SPECIFICATIONS

Output Force (kN)	118
Maximum Input Pressure (bar)	700
Oil Volume Required (cc)	120
Size (mm)	415 (L)
Weight (kg)	9.2

### FEATURES

Cuts steel materials as well as cables up to 55mm. The SP-55A hydraulic cutter head features fast cutting with remote operation.

It can be operated by any hydraulic pump with rated oil pressure of 700 Bar. The blades are easily replaceable and the head is a lock pin type cutter head.

### DETAILS

Cutting of piano wire is prohibited.

Cutting Capacity	
Material	mmOD
Wire rope 6 x 7	25
Wire rope 6 x 12	30
Wire rope 6 x 19	30
Soft steel bar	22
Rebar (400 to 500Mpa)	19
Rebar (650Mpa)	12.4
Cu strands	50
Al strands	50
ACSR	50
Guy wire 1 x 7	15
Guy wire 1 x 19	20

## MODEL No. P-60



**INCLUDED ITEMS**  
Cutter & Carry Bag

### SPECIFICATIONS

Output Force (kN)	79
Maximum Input Pressure (bar)	700
Oil Volume Required (cc)	71
Maximum Opening (mm)	60
Size (mm)	410 (L)
Weight (kg)	5.2

### FEATURES

The P-60 portable hydraulic cutter head cuts Al/Cu cables up to 60mmOD and features fast cutting action with remote operation.

Guillotine type cutting for less jamming than shear type cutting. It can be operated by any hydraulic pump with rated oil pressure of 700 Bar. The blades are easily replaceable and is a lock pin type cutter head.

### DETAILS

Cutting of piano wire is prohibited.

Cutting Capacity	
Material	mmOD
Cu strands	60
Al strands	60
CCP cable	60

- Refer page 116–117 for hydraulic coupling configurations and hoses, supplied standard with screw type female 3050-3 coupling
- Battery or Electric pumps, refer page 106 to 112