

DURAPAC **HYDRAULIC COUPLINGS** OFFER THE USER VARIOUS OPTIONS FOR EASY ASSEMBLY AND CONNECTION OF HYDRAULIC SYSTEMS AND TOOLS.

The CR-6 female high flow screw coupling with dust cap is standard supply on all Durapac cylinders. Other options available include 1/8" and 1/4" screw style couplings and snap together style where no oil spill on connection or disconnection is desirable. The GCS-210 is a gauge coupling set and is ideal for use when the pressure gauge needs to be removed from a system for protection and transportation.

D
SYSTEM ACCESSORIES



THREAD SIZES
1/4", 1/8" & 3/8"-NPT
1/4" & 3/8"-BSPP

MAXIMUM OPERATING PRESSURE
700 bar

CH-2

1/8" male coupling with dust cap* (1/8"-NPT male)

CR-2

1/8" female coupling with dust cap* (1/8"-NPT male)

CS-2

Coupling set with dust caps* includes CH-2 and CR-2

CH-4

1/4" male coupling with dust cap* (1/4"-NPT female)

CR-4

1/4" female coupling with dust cap* (1/4"-NPT male)

CS-4

Coupling set with dust caps* includes CH-4 and CR-4

CH-6

3/8" male coupling with dust cap* (3/8"-NPT female)

CR-6

3/8" female coupling with dust cap* (3/8"-NPT male)

CS-6

3/8" coupling set with dust caps includes CH-6 and CR-6

UDC-1

Universal dust cap to suit 3/8" male and female couplings

CFH-6

Male half snap coupling with dust cap (3/8"-NPT female)

CFR-6

Female half snap coupling with dust cap (3/8"-NPT female)

CFS-6

Snap coupling set with dust caps includes CFH-6 and CFR-6

GCS-210

Gauge coupling set with dust caps. Compact pin design

1/4"-NPT male
1/4"-NPT female

* Dust cap not shown