







NEW AND IMPROVED IZUMI RANGE OF 7 SERIES TOOLS

We are thrilled to announce that the 7 Series range of battery crimpers, cutters, and multitools is basically complete! The only tool not yet upgraded to the Makita platform is the proven performer SL-C510, which will soon join the 7 Series lineup as the perfect final addition.

The new 7 Series tools from Izumi seamlessly blend Japanese craftsmanship with cutting-edge technology, offering unmatched performance. Featuring an innovative brushless motor, these tools provide exceptional precision, reliability, and long-lasting power. Paired with Makita's widely available batteries, the 7 Series tools combine ultimate versatility with consistent performance.

Key Features:

- Brushless Motor for superior efficiency and durability
- Makita Battery Compatibility for easy access to power solutions at your local tool store
- Precision Engineering from Izumi, made in Japan, for optimal performance



7 Series tools are designed to give professionals the power, reliability, and peace of mind they need.

INDEX

TOOL	STYLE	HEAD TYPE	CAPACITY (Kn)	IMAGE	PAGE
	INLINE	LATCHED	52 - 62		3
CRIMPERS	INLINE	"C"	120	G	4
	PISTOL	"C" & DIELESS	60 - 120	777	5
	LUNCH BOX	"C" & LATCHED	120 - 134	ميان ميان ميان	6
	5 TONNE SERIES 111	N/A	N/A		7
	5 TOININE SERIES TTT	IV/A	IV/A		
DIES	5 TONNE CEMBRE	N/A	N/A		8
DIES	6 TONNE ROUND	N/A N/A		**************************************	9
	12 TONNE	N/A	N/A	, 00000 , 00000	10 - 13
	INLINE	Guillotine & Scissor	65 - 87	ii	14
	RATCHET	SCISSOR	N/A	ĬĬ	15
CUTTERS	RATCHET	RATCHET	N/A	111	16
	PISTOL	Guillotine & Scissor	60 - 124	لی کی کی کی کے	17
	LUNCH BOX	Guillotine & Scissor	120 - 135	0-2-2-a-2-a-2-a-2-a-2-a-2-a-2-a-2-a-2-a-	18
MULTITOOLS	INLINE & PISTOL	N/A	N/A	Car	19 - 21



NEW INLINE 18V IZUMI 7 SERIES INLINE CRIMPERS



OVERVIEW

The Izumi SLV Series portable, lightweight, fully automatic, self-contained battery-operated compression tool makes it easy to access tight cable joints in narrow control panels. The control buttons can be activated with just one hand, leaving the other hand free to hold the working material.

FEATURES

- Upgraded Electronic Circuit Board
- · Brushless 18V Motor with **Overload Protection**
- · Ergonomic Design for One-Hand Operation
- 180-Degree Swivel Head
- · Pull Pin Head Design
- LED Light to Illuminate Working Area
- Switch Lever to Change Auto Retract/Manual
- Made in Japan
- · Compatible with Makita 18V Batteries
- Manufactured under ISO 9001

STANDARD ACCESSORIES

- Wrist Strap
- · Carry Case

SLV-50M

Tnakitå



5.0At (18VE

SLV-60EM

SLV-60EM

SLV-630M

Tnakitå.

5.0an (18 V/M

OPTIONAL ACCESSORIES

Model No.	Description
BL1850B	Makita 18v 5.0Ah Battery
DC18RC	Makita 230V Battery Charger
DM18M	Makita to Milwaukee Battery Adaptor







BL1850B



SPECIFICATIONS

K'A Maralal Nia	Chala	Jaw	DIES	DIES	Force	Capacity (mm²)		Dimensions	Weight inc.
Kit Model No.	Style	Opening (mm)	type	refer to page/s	to (Kn) at CII		CU	(mm)	BL1850B Battery (kg)
SLV-50M(BB)	Inline Latched	13	#111	7	52	120	150	105 L x 364 H x 76 W	2.9
SLV-261EM(BB)	Inline Latched	15	CEMBRE	8	52	150	185	105 L x 364 H x 76 W	2.9
SLV-60EM(BB)	Inline Latched	18	ROUND	9	60	185	240	115 L x 415 H x 83 W	3.6
SLV-630M(BB)	Inline Dieless	N/A	DIELESS	N/A	61.5	10 -	240	135 L x 431 H x 76 W	4.5

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Crimper, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.



A PROVEN PERFORMER 14.4V INLINE CRIMPER 12T



OVERVIEW

The Izumi SL streamline series hydraulic crimpers were designed for crimping in tight spaces such as switchboards and panels or pre-existing cable termination points. They accept standard 12 tonne "C" compression dies. Despite their lightweight "in-line" compact design, their performance is still equivalent to that of the pistol style Series 6 tools. The number of times crimping can be completed has increased with the inclusion of 4.0 AH BP-84LI batteries.

FEATURES

- The SL-510 is the latched head version of the SL-C510
- Compress conductors up to 400mm²
- · Rapid ram advance mechanism
- Right or left handed operation
- 180° swivel head (SL-C510)
- Manufactured under ISO 9001
- 14.4VDC 4.0Ah Lithium-Ion Batteries with press charge indicator
- 12/24VDC-230VAC charger included ("CC" kit models)
- Sliding pin with lock function prevents head from opening accidentally

STANDARD ACCESSORIES

- Wrist Strap
- · Carry Case

SPECIFICATION

Kit Model No.	SL-C510(CC)
Style	In-Line
Head Type	С
Jaw Opening	42mm
Force	120 (Kn)
Capacity	Max. 300 mm AL Max. 400 mm CU
Dimensions (mm)	521 L x 150 H x 101 W
Reservoir Capacity	153 (cc)
Wt Inc Battery	7.3 (kg)

COMPATIBLE DIES REFER TO PAGES 10 - 13

- 12T Dies 6.0-400mm² CU
- 12T Dies 6.0-300mm² AL

ORDERING INFORMATION

Model No.	Description					
BP-84LI	• 1 x Battery Only					
CH-120	1 x Charging Base,1 x DC Charge Adaptor 12/24VDC1 x AC Charge Adaptor 230VAC					
SL-C510	In-Line Battery Powered Compression Tool only					
SL-C510(CC)	 In-Line Battery Powered Compression Tool 2 x Batteries (BP-84LI) 1 x Charger (CH-120) 					



SL-C510

14.4V BATTERY & 230VAC/12/24VDC CHARGER









12/24VDC BATTERY CHARGER ADAPTOR

230V BATTERY CHARGER ADAPTOR





· Carry Case

OPTIONAL ACCESSORIES

Model No.	Description
BL1850B	Makita 18v 5.0Ah Battery
DC18RC	Makita 230V Battery Charger
DM18M	Makita to Milwaukee Battery Adaptor





5.0 AM (18 VA





SPECIFICATIONS

00									
		Jaw	DIES	DIES	Force	Capacit	y (mm²)	Dimensions	Weight inc.
Kit Model No.	Style	Opening (mm)	type	refer to page/s	(Kn)	AL	CU	(mm)	BL1850B Battery (kg)
S7G-C431M(BB)	Pistol "C" Head	31	12T	10 -13	120	300	300	413 L x 286 H x 92 W	7.4
S7G-C510M(BB)	Pistol "C" Head	42	12T	10 - 13	120	300	400	436 L x 286 H x 92 W	7.8
S7G-630M(BB)	Pistol Dieless	18	Dieless	N/A	60	10-	240	401 L x 298 H x 82 W	5.8

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Crimper, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.



12 - 15 TONNE BATTERY HYDRAULIC CRIMPERS

OVERVIEW

The S7L Series Battery Hydraulic Crimpers provide faster advance and retraction speeds than previous generation tools. The patent-pending Auto-Retract feature offers a user-selectable ON/OFF switch for manual or automatic retraction. The new ergonomic grip enhances comfort for both "on-ground" and "hold-on" operations. Portability and handling have been improved, and the crimper now features a larger handle opening with a rocker-type advance/retract switch located on top for convenient one-finger trigger operation. The handle opening and rocker switch are designed to accommodate gloved hands. Additionally, the tool incorporates a built-in foot base with finger indents for easier handling when using both hands.

FEATURES

- · Upgraded Electronic Circuit Board
- Brushless 18V Motor with Overload Protection
- 270° Swivel head
- Manual retract button does not rely on battery
- · LED Light to Illuminate Working Area
- · Ergonomic Design
- · Made in Japan
- · Compatible with Makita 18V Batteries
- · Manufactured under ISO 9001

15T DIES

15 Tonne Hex Die-Set Suits S7L-610M & S7L-C610M								
Model No.	mm²	A/F	Material	Crimp Width				
15T-26.0AFCU	300	26.0	CU	10.5mm				
15T-28.1AFCU	400	28.1	CU	8.5mm				
15T-31.0AFCU	500	31.0	CU	7.2mm				
15T-37.0AFCU	630	37.0	CU	6.2mm				
15T-39.0AFAL	400/500	39.0	AL	16.5mm				



15T-PU-ADAPTOR Accepts existing 12 tonne Standard Dies Nest/Indent & "C" connector Dies.

STANDARD ACCESSORIES

- Shoulder Strap
- · Carry Case

OPTIONAL ACCESSORIES

Model No.	Description
BL1850B	Makita 18v 5.0Ah Battery
DC18RC	Makita 230V Battery Charger
DM18M	Makita to Milwaukee Battery Adaptor

S7L-510M Lunch Box "C" Head S7L-C610M Lunch Box "C" Head S7L-610M Lunch Box "C" Head









SPECIFICATIONS

Kit Model No.	Style	Force (kN)	Jaw Opening (mm)	DIES type	DIES refer to page/s	Capacity AL	(mm²)	Dimensions (mm)	Weight inc. BL1850B Battery (kg)
S7L-431M(BB)	Lunch Box "C" Head	120	31	12T	10 - 13	300	300	486 L x 263 H x 92 W	7.7
S7L-510M(BB)	Lunch Box "C" Head	120	42	12T	10 - 13	300	400	508 L x 263 H x 92 W	8.0
S7L-C610M(BB)	Lunch Box "C" Head	134	50	15T	10 - 13	400/500	630	574 L x 263 H x 108 W	10.6
S7L-610M(BB)	Lunch Box Latched	134	50	15T	10 - 13	400/500	630	542 L x 263 H x 94 W	9.0

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Crimper, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.




DIES 5 TONNE SERIES 111 (TO SUIT SLV-50M INLINE CRIMPER)



Model No.	Dimensions Of	Hex Die (mm)	Ctudo	Application			
woder No.	A/F	Crimp Length	Style				
		Copper					
5T-111-5763CU/1	5.7	12	2	10 mm² Cu (Lugs & Links)			
51-111-5/6360/1	6.3	12	2	16 mm² Cu (Lugs & Links)			
5T-111-7792CU/1	7.7	12	2	25 mm² Cu (Lugs & Links)			
51-111-//9200/1	9.2	12	2	35 mm² Cu (Lugs & Links)			
5T-111-	10.4	0	2	50 mm² Cu (Lugs & Links)			
104115CU/1	11.5	9	2	70 mm² Cu (Lugs & Links)			
5T-111-142CU/1	14.2	6	1	95 mm² Cu (Lugs & Links)			
5T-111-165CU/1	16.5	6	1	120 mm² Cu (Lugs & Links)			
5T-111-148CU/1	14.8	6	1	19/2.00 OH			
5T-111-183CU/1	18.3	5	1	150 mm² Cu (Lugs & Links)			
5T-111-200CU/1	20.0	5	1	185 mm² Cu (Lugs & Links)			
		Aluminium					
5T-111-140173AL/1	14.0	9	2	25mm ABC			
51-111-1401/3AL/1	17.3	9	2	35-70mm ABC			
5T-111-180190AL/1	18.0	9	2	Full tension sleeve on 7/3.00 and 7/3.75			
51-111-18019UAL/1	19.0	9	2	Full tension sleeve on 7/4.50			
5T-111-210AL/1	21.0	9	1	Non tension sleeve on 19/3.75 also 120 mm CCT			
5T-111-215AL/1	21.5	9	1	95-150mm ABC			
5T-111-220AL/1	22.0	9	1	Full tension sleeve on 19/3.75			

Each die has dual markings cable size mm² and A/F hex. Note: Each die set consists of 2 pieces





DIES 5 TONNE CEMBRE (TO SUIT SLV-261EM INLINE CRIMPER)



Model No.	A/F Dimension	Description	Tool					
Aluminium								
5T-M90-50	9.00mm	9.0 AF AL	SLV-261EM					
5T-M132-50	13.20mm 50-70mm ²	13.2 AF AL	SLV-261EM					
5T-M140-50	14.00mm 7/2.25 UTILUX 25mm ² ABC	14.0 AF AL	SLV-261EM					
5T-M173-50	17.30mm 95-120mm ²	17.3 AF AL	SLV-261EM					
5T-M215-50	21.50mm 150-185mm ² UTILUX 35-70mm ² ABC	21.5 AF AL	SLV-261EM					
5T-M220-50	22.00mm 19/3.25 CABAC 95-120mm² ABC	22.0 AF AL	SLV-261EM					
	Copper							
5T-M63-50	6.30mm 16mm ²	6.3 AF CU	SLV-261EM					
5T-M77-50	7.70mm 25mm²	7.7 AF CU	SLV-261EM					
5T-M87-50	8.70mm SPECIAL	8.7 AF CU	SLV-261EM					
5T-M92-50	9.20mm 35mm²	9.2 AF CU	SLV-261EM					
5T-M96-50	9.60mm 7/2.00 & 7/2.03	9.6 AF CU	SLV-261EM					
5T-M104-50	10.40mm 50mm²	10.4 AF CU	SLV-261EM					
5T-M115-50	11.50mm 70mm²	11.5 AF CU	SLV-261EM					
5T-M142-50	14.20mm 95mm²	14.2 AF CU	SLV-261EM					
5T-M148-50	14.80mm 19/2.00 O/HEAD 19/2.11	14.8 AF CU	SLV-261EM					
5T-M165-50	16.50mm 120mm ²	16.5 AF CU	SLV-261EM					
5T-M183-50	18.30mm 150mm²	18.3 AF CU	SLV-261EM					
5T-M190-50	19.00mm SPECIAL	19.0 AF CU	SLV-261EM					
5T-M200-50	20.00mm 185mm²	20.0 AF CU	SLV-261EM					
	Cutting E	Die						
5T-MB52-50	10.00mm CUT	STAY WIRE CUTTING DIE 10.0mm O.D.	SLV-261EM					





6 TON ROUND DIES



SUITS KLAUKE EK425, IZUMI SLV-ND, SLV-60EM **DOES NOT SUIT IZUMI 5 TONNE TOOLS**

COPPER

Model No.	Dimensions Of	Dimensions Of Hex Die (mm)						
wodei wo.	A/F Crimp Length		Conductor Details (mm ²)					
6T-6.3AFCU	6.3	6.0	16					
6T-7.7AFCU	7.7	10.0	25					
6T-9.2AFCU	9.2	10.0	35					
6T-10.4AFCU	10.4	9.0	50					
6T-11.5AFCU	11.5	9.0	70					
6T-14.2AFCU	14.2	6.0	95					
6T-16.5AFCU	16.5	6.0	120					
6T-18.3AFCU	18.3	5.0	150					
6T-20.0AFCU	20.0	5.0	185					
6T-23.1AFCU	23.1	5.0	240					
6T-CUSET240	COPPER DIE SET	INCLUDES ALL DIES ABOVE						

ALUMINIUM

Madal Na	Dimensions Of	Canduator Dataila (mm²)	
Model No.	A/F	Crimp Length	Conductor Details (mm ²)
6T-9.0AFAL	9.0	12.0	10-35
6T-13.2AFAL	13.2	12.0	50-70
6T-22.0AFAL	22.0	9.0	150-185

ABC - PRE-INSULATED SLEEVES

Model No.	Dimensions Of	Conductor Dataila (mm²)	
wodel No.	A/F	Crimp Length	Conductor Details (mm²)
6T-14.0AFALABC	14.0	9.0	25
6T-17.3AFALABC	17.3	9.0	35-70
6T-21.5AFALABC	21.5	9.0	95-150





6T-CUSET240



DIES ALUMINIUM 12 TONNE

Suitable for ALL brands of 12T Battery, Manual & Remote Head

Hydraulic Compression Tools									
Model No.	Hex A/F	Length Of Crimp Face	Conductor Details						
Aluminium									
12T-9.0AFAL	9.0 mm	22.0 mm	6-35 mm2						
12T-13.2AFAL	13.2 mm	22.0 mm	50-70 mm2						
12T-17.3AFAL	17.3 mm	22.0 mm	95-120 mm2						
12T-21.0AFAL	21.0 mm	18.0 mm	150-185 mm2 UTILUX						
12T-22.0AFAL	22.0 mm	18.0 mm	150-185 mm2 CABAC						
12T-28.4AFAL	28.4 mm	18.0 mm	240-300 mm2						
		Overhead							
12T-14.0AFAL	14.0 mm	22.0 mm	7/2.25 UTILUX						
12T-14.5AFAL	14.5 mm	22.0 mm	7/2.50						
12T-18.0AFAL	18.0 mm	22.0 mm	7/3.00 & 7/3.75 CABAC						
12T-18.3AFAL	18.3 mm	22.0 mm							
12T-19.0AFAL	19.0 mm	22.0 mm	7/4.50 CABAC						
12T-22.0AFAL	22.0 mm	18.0 mm	19/3.25 CABAC						
12T-26.2AFAL	26.2 mm	18.0 mm	19/3.75 CABAC						
12T-30.3AFAL	30.3 mm	18.0 mm	19/4.75						
		ABC							
12T-14.0AFALABC	14.0 mm	9.0 mm	25 mm2 ABC						
12T-17.3AFALABC	17.3 mm	9.0 mm	35 - 70 mm2 ABC						
12T-21.5AFALABC	21.5 mm	9.0 mm	95 - 150 mm2 ABC						
12T-25.0AFALABC	25.0 mm	8.0 mm	ABC						
		Specials							
12T-7.7AFAL	7.7 mm	25.0 mm	0						
12T-16.5AFAL	16.5 mm	22.0 mm	DIES						
12T-21.5AFAL	21.5 mm	18.0 mm	DIES 0.5kg						
12T-24.9AFAL	24.9 mm	18.0 mm	APPRÖX						
12T-30.0AFAL	30.0 mm	18.0 mm							
		Steel							
12T-7.5AFST	7.5 mm	10 mm	INNER STEEL (ACSR)						
12T-9.5AFST	9.5 mm	10 mm	INNER STEEL (ACSR)						
Neet & Indent Sizes For #IIC! Aluminium Sector Cable									

Nest & Indent Sizes For "UG" Aluminium Sector Cable							
Conductor	:	3 Core	4 Core				
Size	Nest	Indent	Nest	Indent			
70mm ²	12T-12NEST	12T-INDENT14	12T-14NEST	12T-INDENT14			
95mm²	12T-12NEST	12T-INDENT15	12T-14NEST	12T-INDENT15			
120mm²	12T-12NEST	12T-INDENT16	12T-14NEST	12T-INDENT16			
150mm ²	12T-12NEST	12T-INDENT17	12T-15NEST	12T-INDENT17			
185mm²	12T-12NEST	12T-INDENT18	12T-15NEST	12T-INDENT18			
240mm ²	12T-12NEST	12T-INDENT19	12T-15NEST	12T-INDENT19			
300mm ²	12T-12NEST	12T-INDENT20	12T-15NEST	12T-INDENT20			

CUTTING DIE	Description	
12T-CUTTINGDIE	Guy Wire/Guy Strand/EHS Guy Wire, ACSR/AL/CU Ground Rod & Soft Steel Bolts	16mm (5/8") 17.5mm 16mm (5/8")
PLEASE NOTE:	THIS CHART IS A GUIDE ONLY, PLEASE CHE	CK WITH

THIS CHART IS A GUIDE ONLY, PLEASE CHECK WITH YOUR LUG/LINK MANUFACTURER FOR AF SIZES





STEEL STORAGE BOX WITH FOAM INSERT

(15 DIE CAPACITY) MODEL No. 12T-METAL-BOX



PLASTIC STORAGE BOX ALSO AVAILABLE

(18 DIE CAPACITY) MODEL No. 12T-BOX







DIES ALUMINIUM & SETS 12 TONNE

Suitable for ALL brands of 12T Battery, Manual & Remote Head **Hydraulic Compression Tools**

Tydraulic Compression Tools										
Model No.	Hex A/F	Length Of Crimp Face	Conductor Details							
	Copper									
12T-4.4AFCU	4.4 mm	6.35 mm	6 mm2							
12T-5.7AFCU	5.7 mm	6.35 mm	10 mm2							
12T-6.3AFCU	6.3 mm	17.5 mm	16 mm2 *							
12T-7.7AFCU	7.7 mm	17.5 mm	25 mm2 *							
12T-9.2AFCU	9.2 mm	17.5 mm	35 mm2 *							
12T-10.4AFCU	10.4 mm	17.5 mm	50 mm2 *							
12T-11.5AFCU	11.5 mm	17.5 mm	70 mm2 *							
12T-14.2AFCU	14.2 mm	17.5 mm	95 mm2 *							
12T-16.5AFCU	16.5 mm	14.0 mm	120 mm2 *							
12T-18.3AFCU	18.3 mm	14.0 mm	150 mm2 *							
12T-20.0AFCU	20.0 mm	14.0 mm	185 mm2 *							
12T-23.1AFCU	23.1 mm	10.0 mm	240 mm2 *							
12T-26.0AFCU	26.0 mm	10.0 mm	300 mm2 *							
12T-28.1AFCU	28.1 mm	8.0 mm	400 mm2 **							
	Overhead									
12T-8.3AFCU	8.3 mm	9.0 mm	7/1.63 & 7/1.70							
12T-9.6AFCU	9.6 mm	9.0 mm	7/2.00 & 7/2.03							
12T-11.5AFCU	11.5 mm	9.0 mm	7/2.62							
12T-13.0AFCU	13.0 mm	17.5 mm	37/.064 19/2.11							
12T-14.8AFCU	14.8 mm	9.0 mm	19/2.0 & 19/2.11							
12T-19.3AFCU	19.3 mm	14.0 mm	19/2.57							
	Copper Scre	en								
12T-12.7AFCU	12.7 mm	14.0 mm	185mm2 TRIPLEX							
12T-7.5AFCU	7.5 mm	16.0 mm	35mm2 TRIPLEX							
	Specials									
12T-8.7AFCU	8.7 mm	17.5 mm	SPECIAL							



STEEL STORAGE BOX WITH FOAM INSERT

(15 DIE CAPACITY) MODEL No. 12T-METAL-BOX



PLASTIC STORAGE BOX ALSO AVAILABLE

(18 DIE CAPACITY) MODEL No. 12T-BOX

DIE SETS 12 TONNE

Suitable for ALL brands of 12T Battery, Manual & Remote Head Hydraulic Compression Tools

								Con	per				Copper					Aluminium					
Individual Die Orderir	ng Code:	S	12T-6.3AFCU	12T-7.7AFCU	12T-9.2AFCU	12T-10.4AFCU	12T-11.5AFCU	12T-14.2AFCU	12T-16.5AFCU	12T-18.3AFCU	12T-20.0AFCU	12T-23.1AFCU	12T-26.0AFCU	12T-28.1AFCU	12T-9.0AFAL	12T-13.2AFAL	12T-17.3AFAL	12T-21.0AFAL	12T-22.0AFAL	12T-28.4AFAL			
Hex A/F (mm)			6.3	7.7	9.2	10.4	11.5	14.2	16.5	18.3	20	23.1	26	28.1	6	13.2	17.3	21	22	28.4			
Length Of Crimp Face	e (mm)		17.5	17.5	17.5	17.5	17.5	17.5	14	14	14	10	10	œ	22	22	22	18	18	18			
Conductor Details (mm2)		16	25	35	20	70	95	120	150	185	240	300	400	6-35	50-70	95-120	150-185 UTILUX	150-185 CABAC	240-300			
Die Set Ordering Codes	Case	Pcs		Belo	w are	e th e	indiv	idual	dies	inclu	ıded	in the	give	n Die	e Set	, indi	cated	d with	n a √				
12T-CUSET-MB	Metal	11	✓	√	/	✓	✓	✓	√	/	/	✓	✓										
12T-CUSET	Plastic	11	✓	1	1	/	/	✓	1	1	/	1	✓										
12T-CUSET-MB400HB	Metal	12	✓	/	1	1	/	1	/	1	/	1	/	✓									
12T-CUSET400	Plastic	12	✓	√	/	/	✓	/	/	/	/	/	/	✓									
12T-ALCUSET-MB	Metal	18	√	✓	/	✓	✓	✓	✓	/	/	✓	√	✓	/	✓	✓	/	✓	✓			
12T-ALSET	Plastic	6													√	/	✓	/	✓	✓			
12T-ALSET-MB	Metal	6													√	✓	✓	✓	✓	✓			



MODEL No. 12T- SERIES COPPER "C" CONNECTOR DIES



Die sets are for Copper "C" Connectors which are "C" shaped copper sections for terminating main and tap copper conductors. Our dies are made to the same specifications as Burndy, Cabac and Dulmison/PLP (Preformed Line Products). We also supply a range of Utilux die sets for copper conductor terminations.

CE Madal Na	Equivalent to						
SF Model No	Burndy	Cabac	Dulmison/PLP				
12T-U1011	U1011	HT130-C1011	-				
12T-U997	U997	HT130-C997	-				
12T-UC	UC	HT130-CC	-				
12T-UO & 12T-DU1315	UO	HT130-CO	DU1315				

"AUSTRALIAN MADE"











12T-U1011

12T-U997

12T-UC 12T-UO & 12T-DU1315

DIES FOR "YGHC" STYLE EARTHING CONNECTORS

CAT NO	COPPER COND	UCTOR RANGE	SF Model No	IMAGE
CAT NO.	TAP mm2	RUN mm2	12 TONNE	
YGHC2C2	10~35	10~35	U-C	
YGHC26C2	50~70	16~35	U-O	
YGHC26C26	50~70	50~70	U-O	
YGHC29C26	95~150	16~70	U-997	
YGHC29C29	95~150	95~ 120	U-997	
YGHC34C26	150~240	10~70	U-1011	
YGHC34C29	150~240	95~120	U-1011	
YGHC34C34	150~240	150~240	U-1011	

DIES FOR "YGHR" STYLE EARTHING CONNECTORS

CAT NO.	COPPER COND	UCTOR RANGE	SF Model No	IMAGE
CAT NO.	TAP mm2	RUN mm2	12 TONNE	
YGHR2612	10~35	10~35	U-C	
YGHR26C58	50~70	16~35	U-O	
YGHR26C34	50~70	50~70	U-O	
YGHR26C100	95~150	16~35	U-997	
YGHR29C12	95~150	50~70	U-997	
YGHR29C58	95~150	95~150	U-997	
YGHC34C29	150~240	95~120	U-1011	
YGHC34C34	150~240	150~240	U-1011	

DIES FOR "YGHP" STYLE EARTHING CONNECTORS

CAT NO.	COPPER COND	UCTOR RANGE	SF Model No	IMAGE
CAT NO.	TAP mm2	RUN mm2	12 TONNE	
YGHP2C2	10~35	10~35	U-O	
YGHP29C2	45 400			
YGHP29C26	15~120 (13-15mm ROD)	50~70	U-997	
YGHP29C29		95~120	U-997	
YGHP34C2				
YGHP34C26	150~240 (16-19mm ROD)	50~70	U-998	
YGHP34C29		95~120	U-998	
YGHP34C34		150~240	U-1011	



MODEL No. 12T-CUTTING DIE (MADE IN AUSTRALIA)





"AUSTRALIAN MADE"

Cutting dies manufactured in Australia from high tensile steel billets and heat treated to maximise strength and durability.


CAN BE USED IN

- 12 Tonne Hand Hydraulic Crimping Tools
- 12 Tonne Battery Powered Crimpers
- · Remote Head Hydraulic Crimpers

BENEFITS

- · Less costly than dedicated Cutting Tools
- Simple to install in Crimping Tools
- · Require no adjustment for cutting different materials
- · Heavy duty design with 6 high tensile cap screws.

CAN CUT THE FOLLOWING **MATERIALS**



SHORTER LEGS AT TOP TO ALLOW PLACEMENT **BUT STILL CAPTURE MATERIAL**



LONGER LEGS AT BOTTOM TO SUPPORT & CENTRE MATERIAL



NEW INLINE 18V IZUMI 7 SERIES INLINE CUTTERS

OVERVIEW

The Izumi SLV Series Portable, lightweight, versatile battery hydraulic cutters are designed for easy cutting of overhead conductors, underground cables, wires, and ropes. The operation switch is easily activated, leaving your other hand free to align and maneuver the cutting material. 7 Series models feature new electronic circuit boards and improved, powerful gear reduction magnetic motors with overload protection.

FEATURES

- · Upgraded Electronic Circuit Board
- Brushless 18V Motor with Overload Protection
- Ergonomic Design for One-Hand Operation
- 180-Degree Swivel Head
- · Pull Pin Head Design
- · LED Light to Illuminate Working Area
- Switch Lever to Change Auto Retract/Manual
- Made in Japan
- Compatible with Makita 18V Batteries
- Manufactured under ISO 9001

STANDARD ACCESSORIES

- Wrist Strap
- · Carry Case

OPTIONAL ACCESSORIES

Model No.	Description				
BL1850B Makita 18v 5.0Ah Battery					
DC18RC Makita 230V Battery Charger					
DM18M Makita to Milwaukee Battery Adaptor					









BL1850B DM18M



Latch Style

Head





TOOL SPECIFICATIONS

Kit Model No.	Ram Stroke (mm)	Blade Opening (mm)	Dimensions (mm)	Weight inc. BL1850B Battery (kg)
SLV-S24M(BB)	20	24	108 L x 362 H x 76 W	4.1
SLV-Y30M(BB)	40	30	109 L x 412 H x 76 W	3.9

CUTTING SPECIFICATIONS

		Готоо	Maximum Cutting Capacity for Material Type (mm)										
Kit Model No.	Style	Force (kN)	Cuts	Cuts Opening Ø (mm)	Wire Rope	Guy Wire	Steel Bolt	Rebar	AL Strands	CU Strands	ACSR	AL Bar	CU Bar
SLV-S24M(BB)	Inline Guillotine	87	AL/CU/ACSR	24	18	20	18	16	24	24	24	20	18
SLV-Y30M(BB)	Inline Scissor	65	AL/CU/ACSR	30	_	-	-	-	20	20	14	-	-

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Cutter, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.



BATTERY RATCHET SCISSOR CUTTERS (MADE IN JAPAN)

OVERVIEW

The Izumi S7 Series scissor ratchet-style battery cable cutters are designed for cutting both overhead and underground power cables and conductors. The scissor-style design makes it easier to access cables in tight spaces. The rocker trigger switch can be easily operated with one hand, leaving the other hand free to align and maneuver the cutting material. For added safety, the trigger includes a dead-man button to prevent accidental operation. The models feature new electronic circuit boards, improved powerful gear reduction, and brushless motors with overload protection.

FEATURES

- Upgraded Electronic Circuit Board
- Brushless 18V Motor with Overload Protection
- New Auto Reverse feature for Continuous Cutting
- The auto reverse adjust knob allows the dial to adjust the reverse distance according to the cable outer diameter (O.D.)
- · LED Light to Illuminate Working Area
- · Ergonomic Design
- Made in Japan
- · Compatible with Makita 18V Batteries
- · Manufactured under ISO 9001

STANDARD ACCESSORIES

- Wrist Strap
- · Carry Case

OPTIONAL ACCESSORIES

Model No.	Description			
BL1850B Makita 18v 5.0Ah Battery				
DC18RC	Makita 230V Battery Charger			
DM18M Makita to Milwaukee Battery Adapto				









BL1850B **DM18M**

Tnakitå 5.0AH (18V DITH **S7-KY33**M makita 5.0Ah (18V DITHI S7-K50YM

TOOL SPECIFICATIONS

Kit Model No.	Dimensions (mm)	Weight inc. BL1850B Battery (kg)
S7-KY33M(BB)	145 L x 365 H x 116 W	3.3
S7-KY50M(BB)	145 L x 380 H x 116 W	3.6

CUTTING SPECIFICATIONS

ı				Opening Ø		Maximum Cutting Capacity for Material Type				
	Kit Model No.	Style	Cuts	Opening Ø (mm)	AL	cu	ACSR			
	S7-KY33M(BB)	Scissor Ratchet	AL/CU/ACSR	33	33 O.D. mm	33 O.D. mm	18.6 mm			
	S7-K50YM(BB)	Scissor Ratchet	AL/CU	50	630mm ²	500mm ²	N/A			

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Cutter, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.



SPECIALISED FORCEQuality Products, Service and Solutions for 700Bar Hydraulic, Electrical, Rall & Other Key Industries,

BATTERY RATCHET CUTTERS (MADE IN JAPAN)

IZUMI

OVERVIEW

The Izumi S7 Series ratchet-style battery cable cutters are designed for cutting both overhead and underground power cables and conductors. The scissor-style design makes it easier to access cables in tight spaces. The rocker trigger switch can be easily operated with one hand, leaving the other hand free to align and maneuver the cutting material. For added safety, the trigger includes a dead-man button to prevent accidental operation. The models feature new electronic circuit boards, improved powerful gear reduction, and brushless motors with overload protection.

FEATURES

- · Upgraded Electronic Circuit Board
- · Brushless 18V Motor with Overload Protection
- New Auto Reverse feature for Continuous Cutting
- The auto reverse adjust knob allows the dial to adjust the reverse distance according to the cable outer diameter (O.D.)
- · LED Light to Illuminate Working Area
- Ergonomic Design
- Made in Japan
- Compatible with Makita 18V Batteries
- Manufactured under ISO 9001

STANDARD ACCESSORIES

- Wrist Strap
- · Carry Case

OPTIONAL ACCESSORIES

Model No.	Description			
BL1850B Makita 18v 5.0Ah Battery				
DC18RC	Makita 230V Battery Charger			
DM18M	Makita to Milwaukee Battery Adaptor			









BL1850B DI

DM18M

S7-K54ACSRM

S7-K65M

TOOL SPECIFICATIONS

Kit Model No.	Dimensions (mm)	Weight inc. BL1850B Battery (kg)
S7-K50M(BB)	145 L x 318 H x 116 W	2.9
S7-K65M(BB)	145 L x 356 H x 116 W	3.5
S7-K54ACSRM(BB)	145 L x 356 H x 116 W	5.4

5.0AM (18V)

S7-K50M

CUTTING SPECIFICATIONS

Kit Model No.	Stylo	Cuts	Opening	ening Maximum Cutting Capacity for Material Type						
Kit Model No.	Style	Cuts	Ø (mm)	AL	CU	ACSR	Notes			
S7-K50M(BB)	Ratchet	AL/CU	50	630mm ²	500mm ²	N/A				
S7-K65M(BB)	Ratchet	AL/CU	65	630mm ²	630mm ²	N/A	AL (4x240mm²) CU (4x185mm²)			
S7-K54ACSRM(BB)	Ratchet	AL/CU/ ACSR	54	630mm ²	500mm ²	31.5 O.D. mm	ACSR Olive AL 54/3.50 Steel 7/3.50			

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Cutter, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.





TOOL SPECIFICATIONS

DC18RC

BL1850B

ecision & Reliability ets Versatility of

100201201101110110									
Kit Model No.	Dimensions (mm)	Weight inc. BL1850B Battery (kg)							
S7G-K30YM(BB)	393 L x 283 H x 82 W	4.5							
S7G-K105YM(BB)	601 L x 346 H x 92 W	8.9							
S7G-S45M(BB)	444 L x 318 H x 92 W	6.9							
S7G-S24M(BB)	339 L x 281 H x 82 W	5.0							

DM18M

CUTTING SPECIFICATIONS

		Maximum Cutting Capacity for Material Type (m							m)		
Kit Model No.	Style	Force (kN)	Cuts	Opening Ø (mm)	Wire Rope	Guy Wire	Steel Rod/Bolt	Rebar	AL	CU	ACSR
S7G-K30YM(BB)	Scissor	60	AL/CU/ACSR	30	18	20	18	16	24	24	14
S7G-K105YM(BB)	Scissor	124	AL/CU	105	-	-	-	-	105	105	-
S7G-S45M(BB)	Guillotine	70	AL/CU/ACSR	45	22	16	16	-	45	45	32
S7G-S24M(BB)	Guillotine	85	AL/CU/ACSR	24	24	20	16	-	24	24	24

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Cutter, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.



Pin Style Head

S7L-S550M

S7L-K105YM

BATTERY RATCHET CUTTERS (MADE IN JAPAN)

OVERVIEW

The S7L series battery hydraulic cutters can be used for cutting a variety of sizes and types of material. The guillotine-style head cuts up to 40mm in diameter, including CU, AL, ACSR, guy wire, rebar, and wire rope. The scissor-style head cuts up to 105mm in diameter, including polyethylene power cables, multi-core vinyl insulation, and CU and AL conductors.


FEATURES

- Upgraded electronic circuit board
- Brushless 18V motor with overload protection
- · LED Light to Illuminate Working Area
- Manual retract button does not rely on battery
- · Compatible with Makita 18V Batteries
- Ergonomic Design
- Made in Japan
- Manufactured under ISO 9001

STANDARD ACCESSORIES

- Shoulder strap
- · Carry Case

OPTIONAL ACCESSORIES











BL1850B

50B DM18M

TOOL SPECIFICATIONS

Kit Model No.	Dimensions (mm)	Weight inc. BL1850B Battery (kg)
S7L-S550M(BB)	556 L x 263 H x 92 W	10.4
S7L-K105YM(BB)	670 L x 267 H x 99 W	10.5
S7L-S132M(BB)	822 L x 263 H x 92 W	17.3

CUTTING SPECIFICATIONS

	Style	Force (kN)	Cuts	Opening Ø (mm)	Maximum Cutting Capacity for Material Type (mm)								
Kit Model No.					AL	си	ACSR	Wire Rope	Steel Rod/ Bolt				
S7L-S550M(BB)	Lunch Box Guillotine	120	AL/CU/ ACSR	54	50	50	50	30	22				
S7L-K105YM(BB)	Lunch Box Scissor	124	AL/CU	105	105	105	-	-	-				
S7L-S132M(BB)	Lunch Box Guillotine	135	AL/CU	132	130	100	-	-	-				

NOTE: For special cables or conductors contact Specialised Force and we can suggest most suitable models. To order complete kits including Cutter, two Batteries and 230VAC Charger - add the suffix (BB) to the "Kit Model No." shown in tables above.

200AT-410 12-Tonne

Crimp Head Sold Separately

Head Release Pin



6 & 12 TONNE BATTERY HYDRAULIC MULTITOOL



OVERVIEW

The S7G Series Battery Hydraulic 12-tonne pistolstyle multitool is also portable, lightweight, and ergonomically designed.

The SLV Series Battery Hydraulic 6-tonne Inline-style multitool is portable, lightweight, versatile, and ergonomically designed for one-handed operation, making it ideal for use in confined spaces.

With the right attachments (sold separately), these tools can be converted into many different tools, functioning as a cable crimper, cable cutter, angle steel puncher, threaded rod cutter, or knockout puncher.

FEATURES

- Upgraded Electronic Circuit Board
- Brushless 18V Motor with Overload Protection
- Ergonomic Design for One-Hand Operation (Inline)
- Swivel Head
- · Pull Pin Head Design
- · Ergonomic Design
- · Made in Japan
- · Compatible with Makita 18V Batteries
- · Manufactured under ISO 9001

STANDARD ACCESSORIES

- Wrist Strap SLV Series
- Shoulder Strap S7G Series
- · Carry Case

OPTIONAL ACCESSORIES

Model No.	Description
BL1850B	Makita 18v 5.0Ah Battery
DC18RC	Makita 230V Battery Charger
DM18M	Makita to Milwaukee Battery Adaptor









BL1850B DM18M

SPECIFICATIONS

01 2011 1071	110110					
Model No.	SLV-NDM	S7G-MX25OM				
Motor	Brushless 18V	Brushless 18V				
Force at Die Face	70 kN	127 kN				
Head Rotation	180°	275°				
Dimensions (mm)	105 L x 374 H x 80 W	346 L x 328 H x 82 W				
Weight	2.9 kg with BL1850B Battery (without crimp head)	4.0 kg with BL1850B Battery (without crimp head)				



SLV-NDM



CUTTING, CRIMPING & PUNCHING HEADS FOR S7G-MULTITOOL



200AT-410 12 Tonne Crimp Head	200AT-50YC Cable Cutter Attachment	200AT-13WT Threaded Rod Cutter Attachment				
 Opening Between Die Faces: 17mm Maximum Capacity: 300mm² (AL/CU) Weight: 2.4kg Accepts existing 12-ton U-type Dies Refer to Page/s: 10-13 for 12T Dies 	Cutting Capacity: Up to 50mm O.D. Cable (Including Insulation) Cuts nonferrous cables only Weight: 1.0kg	Cut: M10 or 3/8 BSW Steel or SS Threaded Rod M12 or 1/2 BSW Steel or SS Threaded Rod Includes: 13WT-07 M12 Blade Set Optional Blade Sets: 13WT-06 M10 13WT-02 3/8 BSW 13WT-05 1/2 BSW				

200AT-AP18 Angle Steel Puncher Attachment

- Supplied with 3 sets of Punch Dies (Max capacity: 6mm Mild Steel):
 - 10.5mm Diameter
 - 13.5mm Diameter
- 17.5mm Diameter
- Size (mm): 186 L x 130 H x 67 W
- · Weight: 3.8kg
- Throat Depth: 47mm
- To Centre of Punch: 23.5mm

200AT-9PD Knockout Puncher Attachment

- Punching Capacity:
- Up to 63.5 mm diameter hole in Stainless Steel
- Up to 115.5 mm diameter hole in 3.0 mm thick Mild Steel
- Punch & die, Draw Studs & Spacer Collars are the same as those used for SH-10
- 200AT-9PD Comes with Draw Studs & Spacer Collars
- Refer to SF Representative for suitable dies





ORDERING INFORMATION

Model No.	Description	S7G-MX250M	200AT-410 Crimp Head	200AT-50YC Cutting Head	200AT-13WT Cutting Head	200AT-AP18 Punching Head	200AT-9PD Punching Head	BL1850 Makita 18v 5.0Ah Battery	DC18RC Makita 230V Battery Charger
S7G-MX25OM	12T Tool Only	1							
S7G-MX25OM(BB)	12T Tool with Battery & Charger	1						2	1
S7G-MX250M/410(BB)	12T AL/CU Crimping Tool	1	1					2	1
S7G-MX250M/50YC(BB)	12T Cable Cutting Tool	1		1				2	1
S7G-MX25OM/13WT(BB)	12T Threaded Rod Cutting Tool	1			1			2	1
S7G-MX25OM/AP18(BB)	12T Steel Puncher	1				1		2	1
S7G-MX25OM/9PD(BB)	12T Knock out Puncher	1					1	2	1

NOTE: All Tool Combinations Supplied with Case. Contact your Nearest Specialised Force Branch to Design your Own Kit.



CUTTING & CRIMPING HEADS FOR SLV-MULTITOOL



SL-6CJ 6T Crimping Jaw:	SL-CH Cutting Jaw:	SL-ACSR Cutting Jaw:	SL-GW Cutting Jaw:
 Accommodates 6-ton round type dies for crimping Cu, Al, ACSR & ABC. Up to 240mm² Capacity for Al, Cu and ACSR. 	 For cutting Al & Cu. Cutting capacity up to 32mm OD Cu/Al (300mm²). 	 For cutting ACSR. Cutting capacity up to 20mm OD ACSR (Single Steel Core). 	 For cutting AI, Cu & ACSR. Cutting capacity up to 14.3mm for Cu, AI & ACSR.

NOTE: Jaws are sold separately.

CUTTING SPECIFICATIONS

			Cuts	Opening Ø (mm)	Maximum Cutting Capacity for Material Type (mm)*										
Kit Model No.	Style	Force (kN)			Wire Rope 6x7	Wire Rope 6x12	Wire Rope 6x19	Soft Steel Bar	ReBar (400 to 500 Mpa)	Rebar (650Mpa)	AL Strands	CU Strands	ACSR	Guy Wire 1x7	Guy Wire 1x19
SLV-ND/ACSR(BB)	Scissor	70	AI/Cu/ ACSR	21	N/A	N/A	N/A	N/A	N/A	N/A	14	14	20	N/A	N/A
SLV-ND/CH(BB)	Scissor	70	Al/Cu	32	N/A	N/A	N/A	N/A	N/A	N/A	32	32	N/A	N/A	N/A
SLV-ND/GW(BB)	Scissor	70	AI/Cu/ ACSR	19.5	N/A	N/A	N/A	9.3	9.3	N/A	14.3	14.3	14.3	9.3	9.3

ORDERING INFORMATION CUTTERS

Kit Model No.	Ram Stroke (mm)	Blade Opening (mm)	Reservoir Capacity (BB)	Dimensions (mm)	Weight Including Battery (kg)
SLV-ND/ACSR (BB)	-	21	45	554L x 110H x 80W	3.5
SLV-ND/CH(BB)	-	32	45	554L x 110H x 80W	3.5
SLV-ND/GW(BB)	-	19.5	45	554L x 110H x 8W	3.5

ORDERING INFORMATION CRIMPERS

Model No.	Description	SLV-NDM Tool Only	SL-6CJ Crimp Head	SL-CH AL/CU Cutting Head	SL-ACSR ACSR Cutting Head	SL-GW AL/CU/ACSR Cutting Head	BL1850 Makita 18v 5.0Ah Battery	DC18RC Makita 230V Battery Charger	6T-6mm Rounding Die	SL-CB Bending Tool
SLV-NDM	6T Tool Only	1								
SLV-NDM(BB)	6T Tool with Battery & Charger	1					2	1		
SLV-NDM/6CJ(BB)	6T Crimping Tool	1	1				2	1		
SLV-NDM/CH(BB)	6T AL/CU Cutting Tool	1		1			2	1		
SLV-NDM/6CJ/ACSR(BB)	6T Crimping & ACSR Cutting Tool	1	1		1		2	1		
SLV-NDM/ACSR(BB)	6T ACSR Cutting Tool	1			1		2	1		
SLV-NDM/GW(BB)	6T AL/CU/ACSR Cutting Tool	1				1	2	1		
SLV-NDM FENCING TOOL	6T Fencing Tool	1	1				2	1	1	
SLV-NDM/CB(BB)	6T Cable Bending Tool	1					2	1		1

NOTE: All Tool Combinations Supplied with Case. Contact your Nearest Specialised Force Branch to Design your Own Kit. Refer to Page/s: 9 for 6T Crimping Dies.

Townsville (07) 4728 8756



• Established 1982

Australian Owned and Operated

Locations Australia Wide

COMPANY PROFILE

Specialised Force Pty Ltd has been operating and expanding throughout Australia since 1982. With the Head office in Sydney, the company now operates in Brisbane, Townsville, Darwin, Adelaide, Melbourne, Perth, Port Hedland and Hobart, with additional support distribution network covering all areas throughout Australia & New Zealand for over 40 years.

Specialised Force success rests on unique knowledge of specialised hydraulic, electrical tooling equipment and other products. This includes synchronised lifting systems, torque equipment, heat exchanger, pipe maintenance equipment and overhead/underground power installation equipment. We pursue a "complete system" approach and carefully match components to ensure efficient and safe operation of equipment. In order to transform this knowledge into solutions that meet demands in different industries, the company is organised into separate business areas

FOCUSED BUSINESS AREAS

- ELECTRICAL Overhead & Underground Power Installation Machinery & Equipment
- RAIL Maintenance, Construction and Safety Equipment
- MINING Jacking, Maintenance Tools & Tensioning Devices
- OIL & GAS Flange Maintenance, Alignment, Spreading & Torque Tools
- CIVIL INFRASTRUCTURE Bending, Crimping, Punching & Cutting Tools
- INDUSTRIAL Heavy Load Lifting/Shifting, Maintenance & Safety Equipment
- **COMMUNICATIONS** Drum Handling Equipment, Rollers & Winches
- TRANSPORT Jacks, Presses, Pullers, Repair Kits & Torque Tooling

Safety First

Specialised Force strives to provide a safe, healthy work environment that stimulates customers and employees to perform effectively, to assume responsibility and to continue to develop towards company goals. Specialised Forces vision is for zero work-related injuries.

Environmental Responsibility

Environmental consideration is a key element in our operations. We strive to prevent or minimize harmful effects on the environment.

Driven By Customer Value

Where businesses are evolving – that's where you'll find Specialised Force. Our range of products and solutions are used by customers worldwide and by most industries. Specialised Force offers improved efficiency, productivity and safety, which in turn boosts profitability for customers.

OUR KEY VALUES



Excellence:

We apply advanced technology and continually innovate and improve.



Safety:

Zero accidents is our unwavering goal



Fair Return:

We earn a return that fairly rewards the value we deliver



Sustainability:

We plan and act for the future - considering our company, our customers and our world.



Uncompromising integrity, honest and fairness are at the heart of our company.

TERMS AND CONDITIONS

The content of this catalogue is provided for information only and without responsibility. SPECIALISED FORCE PTY LTD makes no representations about the accuracy, reliability, completeness, or timeliness of the information in his catalogue. SPECIALISED FORCE PTY LTD may, in its sole discretion, revise the information contained herein at any time without notice. SPECIALISED FORCE PTY LTDs obligations and responsibilities regarding its products are governed solely by the agreements under which they are sold. Unless otherwise agreed in writing, the information contained herein does not become part of these agreements. This catalogue does not contain any guarantee or agreed quality of SPECIALISED FORCE PTY LTD's products or any warranty of merchantability, fitness for a particular purpose, or non-infringement. SPECIALISED FORCE PTY LTD may make changes in the products or services described at any time

SPECIALISED FORCE PTY LTD is not liable for any direct, indirect, incidental, consequential, or punitive damages arising out of the use of this catalogue. SPECIALISED FORCE PTY LTD reserves the right to supply alternative products at its discretion. The trademarks, service marks, and logos (the Trademarks) displayed in this catalogue are the property of SPECIALISED FORCE PTY LTD and/or its affiliates. Nothing in this catalogue should be construed as granting any license or right to the Trademarks. Without the express written consent of SPECIALISED FORCE PTY LTD, the use of the Trademarks is prohibited.

All text, images, graphics, and other materials in this catalogue are subject to the copyright and other intellectual property rights of SPECIALISED FORCE PTY LTD and/or its affiliates. These materials may not be modified or copied for commercial use or distribution. Copyright © 2024. All rights reserved.

Adelaide (08) 8352 8866 Brisbane (07) 3256 6011 **SYDNEY Head Office** (02) 9547 1844 Townsville (07) 4728 8756 Darwin (08) 8984 4453 Melbourne (03) 9761 4199 Perth (08) 9354 8544 Port Hedland (08) 9172 1113 Tasmania 0427 423 217



BARE CONDUCTORS TYPE ACSR/GZ (ALUMINIUM CONDUCTORS, **GALVANISED STEEL REINFORCED MANUFACTURED TO AS 3607)**



Codename	Stranding	& Wire	Nominal	Cross-	Approx.	A/F Across Flat (mn		Breaking	
& Product Code	Aluminium OD (no/mm)	Steel OD (no/mm)	OD (mm)	Sectional Area (mm2)	Mass (kg/ km)	A/F Aluminium Outer	A/F Steel Inner	Load (kN)	
Almond	6/2.50	1/2.50	7.5	34.4	119	14.00	6.80	10.5	
Apricot	6/2.75	1/2.75	8.3	41.6	144			12.6	
Apple	6/3.00	1/3.00	9.0	49.5	171	14.00	6.80	14.9	
Banana	6/3.75	1/3.75	11.3	77.3	268	18.00	9.50	22.7	
Cherry	6/4.75	7/1.60	14.3	120.0	402	22.00	9.50	33.4	
Grape	30/2.50	7/2.50	17.5	182.0	677	28.50	16.00	63.5	
Lemon	30/3.00	7/3.00	21.0	262.0	973	34.50	17.00	90.4	
Lychee	30/3.25	7/3.25	22.8	307.0	1140			105.0	
Lime	30/3.50	7/3.50	24.5	356.0	1320	40.00	19.00	122.0	
Mango	54/3.00	7/3.00	27.0	431.0	1440	40.00	17.00	119.0	
Orange	54/3.25	7/3.25	29.3	506.0	1690	44.50	19.00	137.0	
Olive	54/3.50	7/3.50	31.5	587.0	1960	47.50	19.00	159.0	
Pawpaw	54/3.75	19/2.25	33.8	672.0	2240	47.50	20.00	178.0	
Quince	3/1.75	4/1.75	5.3	16.8	95			12.7	
Raisin	3/2.50	4/2.50	7.5	34.4	195			24.4	
Sultana	4/3.00	3/3.00	9.0	49.5	243			28.3	
Walnut	4/3.75	3/3.75	11.3	77.3	380			43.9	

POWER CABLE DIMENSIONAL DATA

	DIM	ENSIONAL I	DATA		DIE SIZE	A/F (mm)					Cable	Types				
Cross Sectional	Stranding (No / Wire	OD of	Imperial Equivalent	AWG Size (American	Cu Die	Al Die	PVC	Insulated Sheathed	XLPE / PVC	Mult	iple Core C	ables (0.6/	′1kV)	XLPE	/ URD	Name
Area	Diameter	Conductor	(No/Wire	Wire	(A/F)	(A/F)	•	•	•	••	••	• • •	• • • •	• •	• •	Cores
(mm2)	Ø mm)	(mm)	Diameter Ø)	Gauge)	(, ,	(41)					\checkmark	\checkmark	✓			Earth
1	1/1.13	1.1	1/.044	18		-	3.0	4.0	-	10.0	-	-	-			
	7/0.40	1.2														
1.5	1/1.3	1.4	3/.029	16	-	-	3.5	4.5	-	11.5	8.5	7.5	10.5			
	7/0.50	1.5	1/.064													
2.5	7/0.67	2.0	3/.036 7/.029	14	-	-	4.0	5.0	-	12.0	8.0	11.5	12.5			
4	7/0.85	2.6	7/.036	12	-	-	4.5	6.0	-	13.5	11.5	15.5	19.0		St	
6	7/1.04	3.1	7/.044	9	4.4	9.0	5.5	7.0	-	14.5	12.5	16.5	15.0	Solid	ranc	
10	7/1.35	4.1	7/.052	7	5.7	9.0	6.0	8.0	-	17.0	17.0	18.5	20.0	9 0	ded a	
16	7/1.70	5.1	7/.064 19/.044	5	6.3	9.0	7.0	9.0	9.5	19.0	19.0	20.5	23.0	Conductor	Stranded Conductor	
25	19/1.35	6.8	19/.052	3	7.7	9.0	8.5	11.0	10.5	23.0	22.0	24.0	26.5	Ť	tor	
35	19/1.53	7.7	19/.064	2	9.2	9.0	9.5	12.0	11.5	-	25.0	26.5	29.5			Approx
50	19/1.7	8.9	19/.072	1/0	10.4	13.2	11.0	14.0	13.0	-	28.0	31.0	35.0			OD of
70	19/2.14	10.7	19/.083	2/0	11.5	13.2	12.5	15.5	15.0	-	32.0	35.0	39.0			Cable
95	37/1.7	12.5	37/.072	3/0	14.2	17.3	15.5	18.0	17.5	-	-	40.0	45.0			
120	37/2.03	14.2	37/.083	250MCM	16.5	17.3	17.5	20.5	20.0	-	-	43.5	50.0			
150	37/2.25	15.8	37/.093	300MCM	18.3	22.0	19.0	24.5	21.5	-	-	48.5	55.0			
185	37/2.52	17.6	37/.103	350MCM	20.0	22.0	21.5	26.5	23.5	-	-	54.0	61.0	43.0	47.5	
240	61/2.25	20.3	61/.093	500MCM	23.1	28.4	24.5	28.0	26.5	-	-	61.0	69.5	50.0	53.5	
300	61/2.52	22.3	61/.103	600MCM	26.0	28.4	27.0	31.0	29.5	-	-	68.0	77.0			
400	61/2.85	25.7	91/.093	800MCM	28.1	39.0	31.0	35.0	33.5	-	-	-	-			
500	61/3.20	28.8	91/.103 127/.093	1000MCM	31.0	39.0	34.5	38.5	37.0	-	-	-	-			
630	127/2.52	32.8	127/.103	1200MCM	37.0	43.2	38.0	42.5	41.5	-	-	-	-			
800	127/2.85	37.0	127/.112	-	43.2	52.5	-	-	-	-	-	-	-			
1,000	127/3.7	41.6	127/.125	-	48.0	52.5	-	-	-	-	-	-	-			









Scan here to see full range of SF Catalogues



Sydney (Head Office)

- 131 Woids Avenue Carlton, NSW 2218
- **8** (02) 9547 1844
- sales@specialisedforce.com.au

Brisbane

- 2/68 Northlink Place Northgate QLD, 4013
- **8** (07) 3256 6011
- gldsales@specialisedforce.com.au

Adelaide

- 23 Ceafield Rd Para Hills West, SA, 5096
- **8** (08) 8352 8866
- sasales@specialisedforce.com.au

Darwin

- O Unit 4/17 Willes Road Berrimah NT, 0828
- **(08)** 8984 4453
- ntsales@specialisedforce.com.au

Port Hedland

- 4/13 Cajarina Road Wedgefield, WA 6721
- **(08)** 9172 1113
- phsales@specialisedforce.com.au

Melbourne

- 2/18 Southfork Drive Kilsyth Vic 3137
- **8** (03) 9761 4199

- O Unit 2/1 Civil Road Garbutt QLD, 4814
- **8** (07) 4728 8756
- ngldsales@specialisedforce.com.au

- 17 19 Augusta Street Willetton, WA 6155
- **(08)** 9354 8544
- wasales@specialisedforce.com.au

Hobart

- Office 22, 370-380 Cambridge Road, Mornington TAS, 7018 Tasmania
- 0427 423 217
- tassales@specialisedforce.com.au

Locations Australia Wide