



MODEL No. HLB-560

Aluminium Hand Line Block

Lightweight aluminium hand line block used for hauling and lifting applications. Comes with top swivelling hook with safety latch. Side opening with ball lock pin secured to body with chain.

SPECIFICATIONS

| Model No. | HLB-560 | HLB-560/P&C |
|----------------------|---------|-------------|
| WLL (kg) | 560 | 560 |
| Max Rope (mm) OD | 14 | 14 |
| Sheave Diameter (mm) | 75 | 75 |
| Gate Latch- Pin Type | R CLIP | DETENT PIN |



| | |
|-------------|--------------------|
| Model No. | PCA1260 |
| WLL (kg) | 2000 |
| Description | 2m Polyester Sling |

SPARE PARTS

| Model No. | Description |
|--------------------|--------------------------------|
| HLB-P&C | Pin & Chain |
| HLB-R/CLIP | Pin & R/Clip |
| HLB-LK | Latch Kit - Spring, Gate & Pin |



LATCH KIT
Model No. **HLB-LK**



PIN & CHAIN
Model No. **HLB-P&C**

MODEL No. BPE-1 PULLING EYE

- For anchor rod pulling
- Large offset eye for 3 tonne shackle or hook
- Allows clearance for attaching formed wire grips
- Slide wedge design allows for a range of rods sizes
- Cast from high strength iron

| Model No. | Anchor Rod Ø (mm) | WLL 5:1 (kg) | Wt (kg) |
|--------------|-------------------|--------------|---------|
| BPE-1 | 13-32 | 2721 | 2.2 |

