

**ANTI-TWISTING STEEL ROPE**



Model Number	<b>21.12</b>
Description	Anti-twisting galvanised steel rope specifically designed for stringing operations. Made up of 12 braided strands. High resistant to break, anti-twisting, flexible, safe and easy to handle. The linear contact between the braided strands grants a low stress on the rope. Supplied wound up on steel or wooden reels.



Model No.	Nominal Diameter (mm)	Breaking Load (kN)	Weight (kg)	Standard Lengths* (m)
<b>21.12.08</b>	8	44	0.22	1000
<b>21.12.10</b>	10	72	0.35	1000
<b>21.12.13</b>	13	105	0.55	1000
<b>21.12.16</b>	16	163	0.80	1000
<b>21.12.18</b>	18	235	1.07	1000
<b>21.12.20</b>	20	268	1.24	1000
<b>21.12.22</b>	22	330	1.56	900
<b>21.12.24</b>	24	380	1.80	800
<b>21.12.28</b>	28	480	2.80	600

\*Other Ropes and Lengths available - Please contact your nearest Specialised Force Branch for further information [www.specialisedforce.com.au](http://www.specialisedforce.com.au)

Model No.	Description	Optional Devices
<b>F162</b>	Welded and painted steel reel, complete with central dials and bolts.	<ul style="list-style-type: none"> <li>• Total galvanization.</li> <li>• Additional pair of standard dials.</li> <li>• Pair of dials equipped with ball bearings</li> <li>• Reinforced reel made of square tubular (30% heavier than the standard version).</li> </ul>
<b>F164</b>	Welded and painted steel conical reel with openable side. Complete with central dials and bolts.	<ul style="list-style-type: none"> <li>• Total galvanization.</li> <li>• Additional pair of standard dials.</li> <li>• Pair of dials equipped with ball bearings.</li> <li>• Drum core covered with steel sheet.</li> </ul>

**STEEL REELS FOR ROPES**

Model No.	Dimensions (mm)						Weight Without Rope (kg)
	A	B	C	D	E	F	
<b>F162.060</b>	700	530	460	219		50	27
<b>F162.110</b>	1100	560	460	570	420	50	66
<b>F162.140</b>	1400	560	460	570	420	50	105
<b>F162.160</b>	1600	560	460	570	420	50	120
<b>F162.190</b>	1900	560	460	570	420	50	140
<b>F162.200</b>	2200	1560	1400	1010	420	100	950
<b>F164.060</b>	700	530	460	219		50	40
<b>F164.110</b>	1100	560	460	570	420	50	85
<b>F164.140</b>	1400	560	460	570	420	50	115
<b>F164.160</b>	1600	560	460	570	420	50	130
<b>F164.190</b>	1900	560	460	570	420	50	220
<b>F164.205</b>	2050	1310	1170	630	420	50	550
<b>F164.220</b>	2200	1310	1170	1010	420	100	1050