

DIGITAL BUILT-IN DATA READ-OUT





Electronic Instrument for monitoring the working values. Fit for OMAC pullers, tensioners and puller-tensioners. A must-have device installed on all OMAC machines as a standard.

Model No.	DEG
Features	 Large Screen allowing for excellent visibility from any angle Graphic, colour display Integrated into the main control panel High capacity memory: Over 200km of line High accuracy and reliability due to load cells and encoder system Equipped with USB port Ease of use
Functions	 Reads & displays pull force, speed & length of cable in real time Max pull force setting Display of working hours Data recording Data storage on a pen-drive Software provided allows for handling the data stored
Optional	



Model No. 069.5

- Portable printer c/w connection cable to be plugged into the machine
- Fit for printing the recorded data directly on the job-site
- Supplied in aluminium case

REMOTE CONTROLS







Model No.	REC.1	REC.2	RER.1
Description	Compact remote control by cable. Fit for "puller" machines with 1 hydraulic circuit. Pull/release buttons and emergency stop button. 10m of connection cable.	Remote circuit by cable. Fit for "puller" machines with 1 hydraulic circuit. The control is complete with: • Mini joystick for controlling the rotation of the capstans • Speed-adjustment control • Emergency stop button • 10m of the connection cable	Remote radio-control fit for single circuit machines. Max operative distance: up to 100m. The radio control is complete with: • Mini joystick for controlling the rotation of the capstans • Speed-adjustment control • Emergency stop button • Back-up cable for connecting the control to the machine in case of emergency
Optional Devices	-	 Dynamometer to read the pulling force, meter counter & speedometer Engine start/stop Engine accelerator 	Dynamometer to read the pulling force, meter counter & speedometer Engine start/stop Engine accelerator