

**CABLE SOCKS - STANDARD TUBULAR CABLE GRIPS (MADE IN AUSTRALIA)**

**C1 SERIES**

**Construction:**

- Two Ply
- Alloy Ferrule
- Galvanised Strand
- Soft Eye



**MOST POPULAR**

SOFT EYE - AL FERRULE Model No.	To fit Cable Diameter (mm)	Grip Length (mm)	Ultimate Tensile Strength (UTS kN)	WLL 3:1 (kN)*
C1010	10-14	350	5	1.7
C1014	14-19	400	9	3.0
C1019	19-28	500	15	5.0
C1028	28-40	600	24	8.0
C1040	40-55	800	35	11.7
C1055	55-75	900	62	20.7
C1075	75-95	1000	98	32.7
C1095	95-120	1200	133	44.3
C1120	120-150	1400	187	62.3
C1150	150-190	1600	283	94.3

<sup>1</sup> Copper ferrule C3 series available for reduced spark environments  
\* WLL (Working Load Limit) 3:1 Recommended as a Guide Only.

**NON-CONDUCTIVE TUBULAR GRIP (MADE IN AUSTRALIA)**

**LV SERIES**

**Construction:**

- Double or Triple Ply
- Alloy Ferrule
- Monofilament Nylon Strand
- Single Eye



**For LV ABC**

Model No.	To fit Cable (mm <sup>2</sup> )	Grip Length (mm)	Ultimate Tensile Strength (UTS kN)	WLL (kN)
LV225	2 x 25mm <sup>2</sup>	600	15	5.0
LV235	2 x 35mm <sup>2</sup>	600	15	5.0
LV250	2 x 50mm <sup>2</sup>	600	15	5.0
LV295	2 x 95mm <sup>2</sup>	600	15	5.0
LV335	3 x 35mm <sup>2</sup>	600	15	5.0
LV395	3 x 95mm <sup>2</sup>	600	25	8.3
LV425	4 x 25mm <sup>2</sup>	600	15	5.0
LV435	4 x 35mm <sup>2</sup>	600	15	5.0
LV450	4 x 50mm <sup>2</sup>	600	15	5.0
LV470	4 x 70mm <sup>2</sup>	800	17	5.6
LV495	4 x 95mm <sup>2</sup>	800	25	8.3
LV4150	4 x 150mm <sup>2</sup>	800	25	8.3

**Note:** WLL (Working Load Limit) 3:1 recommended as a guide only.

**HV SERIES**

**Construction:**

- Double or Triple Ply
- Alloy Ferrule
- Monofilament Nylon Strand
- Double Eye



**For HV ABC**

Model No.	To fit Cable (mm <sup>2</sup> )	Grip Length (mm)	Ultimate Tensile Strength (UTS kN)	WLL (kN)
HV335	3 x 35mm <sup>2</sup>	800	25	8.3
HV350	3 x 50mm <sup>2</sup>	800	25	8.3
HV370	3 x 70mm <sup>2</sup>	800	25	8.3
HV395	3 x 95mm <sup>2</sup>	900	31	10.3
HV3120	3 x 120mm <sup>2</sup>	900	31	10.3
HV3150	3 x 150mm <sup>2</sup>	900	31	10.3
HV3185	3 x 85mm <sup>2</sup>	900	31	10.3

**Note:** WLL (Working Load Limit) 3:1 recommended as a guide only.

OVERHEAD CONSTRUCTION & STRINGING EQUIPMENT

www.specialisedforce.com.au