



## REMOTE HEAD CRIMPER 12 TONNE - Standard 12 Tonne Dies Nest/Indent & "C" Connector Dies



**EP-431HA**




**PINCH FREE MODEL**

**FORCE**  
12 Tonne Type

**JAW OPENING**  
31mm C-HEAD

**CAPACITY**  
300mm<sup>2</sup> Al/Cu



**MAX**  
**300mm<sup>2</sup>**

### MODEL No. EP-431HA

#### INCLUDED ITEMS

Crimp Head, Steel carrying case with die tray

#### SPECIFICATION

Ram Stroke	31mm (Jaw opening)
Oil volume required	50 cc
Force at die face	106 kN
Size	340 (L) mm
Weight	4.75 kg



**EP-510HE**

FITTED WITH A RUBBER BOOT FOR ADDED ELECTRICAL PROTECTION



**PINCH FREE MODEL**

**FORCE**  
12 Tonne Type

**JAW OPENING**  
42mm C-HEAD

**CAPACITY**  
300mm<sup>2</sup> Al & 400mm<sup>2</sup> Cu



**MAX**  
**400mm<sup>2</sup>**

### MODEL No. EP-510HE

#### INCLUDED ITEMS

Crimp Head, Steel carrying case with die tray

#### SPECIFICATION

Ram Stroke	42mm (Jaw opening)
Oil volume required	77 cc
Force at die face	118 kN
Size	420 (L) mm
Weight	5.7 kg

- Battery or Electric pumps, refer page 103-108
- Dies are sold separately, refer page 18-20 for 12T Dies
- Refer page 112-113 for hydraulic coupling configurations and hoses, supplied standard with screw type female 3050-3 coupling



**EP-610HS2**



**FORCE**  
15 Tonne Type

**JAW OPENING**  
40mm with Dies Fitted

**CAPACITY**  
300mm<sup>2</sup> Al & 400mm<sup>2</sup> Cu  
500mm<sup>2</sup> AL & 630mm<sup>2</sup> CU with 15T Dies



**MAX**  
**630mm<sup>2</sup>**

### MODEL No. EP-610HS2

#### INCLUDED ITEMS

Steel carrying case with die tray  
(Accepts existing 12 ton Standard Dies Nest/Indent & "C" connector Dies when used with **15T-PU-ADAPTOR**).

#### SPECIFICATIONS

Ram Stroke	50mm (Jaw Opening)
Oil volume required	100 cc
Force at die face	139kN
Size	375 (L) mm
Weight	7.0 kg

#### DIES & ACCESSORIES

15 Tonne Hex Die-Set Suits Rec-3610				
Model No.	mm <sup>2</sup>	A/F	Material	Crimp Width
<b>15T-26.0AFCU</b>	300	26.0	CU	10.5mm
<b>15T-28.1AFCU</b>	400	28.1	CU	8.5mm
<b>15T-31.0AFCU</b>	500	31.0	CU	7.2mm
<b>15T-37.0AFCU</b>	630	37.0	CU	6.2mm
<b>15T-39.0AFAL</b>	400/500	39.0	AL	16.5mm
Model No.	Description			
<b>15T-PU-ADAPTOR</b>	PICK UP ADAPTOR TO SUIT STANDARD 12TONNE DIES			

