

REMOTE CRIMP HEAD – 60T





Made in

Japan



SPECIFICATION

Ram Stroke	38mm (Jaw opening)
Oil volume required	303 cc
Forced at die face	540 kN at 700 Bar (10,000 PSI) of oil pressure
Dimensions (mm)	146 (Ø) x 450 (h) with ground stand
Weight (kg)	19.8 without Ground Stand
	21.4 with Ground Stand

ACCESSORIES

Optional Die adapter for 12 ton type dies MODEL No. 60T-12T

FEATURES

The EP-60S compression head was designed as a portable tool for installing compression sleeve and terminals for transmission construction and maintenance work.

Suitable For Transmission Line Construction

DETAILS

- Dies are sold separately Refer page 34 for 60T Dies
- Accepts all dies used for Alcoa, 60 ton compressors

SUPPLIED WITH **GROUND STAND &** METAL STORAGE CASE

- Specify the manufacturer's die and connector numbérs
- Portable and light weight
- · Detachable ground stand
- Large handle for easy carrying
- Single acting hydraulic pump required: 700 Bar Working Pressure
- Industry Standard 60 Tonne Classification Head



4

• Refer page 112–113 for hydraulic coupling configurations and hoses, supplied standard with screw type female 3050-3 coupling Battery, Diesel, Petrol or Electric pumps, refer page 103–110