

## MODEL No. S-200A



**INCLUDED ITEMS**  
Cutter & Carry bag

### SPECIFICATIONS

Output Force (kN)	39
Maximum Opening (mm)	22
Reservoir Capacity (cc)	70
Maximum Handle Load (N)	235
Pumping Cycles When No Load	39 times
Single Stage Pumping	
No Relief Valve	
Size (mm)	380 (L)
Weight (kg)	2.8

### FEATURES

**Light weight portable hydraulic cutter features new series, heavy duty improved design.**

Guillotine type cutting jaw is less jamming than shear type cutting jaw. No set-up time is required, the blades are easily replaceable and 180° swivel and latch type head allows easy cutting position.

### DETAILS

Cutting of piano wire is prohibited

Cutting Capacities	
Material	mmOD
Wire rope 6 x 7	16
Wire rope 6 x 12	20
Wire rope 6 x 19	20
Soft steel bar	16
Rebar (400-500Mpa)	13
Rebar (650Mpa)	10
Cu strands	20
Al strands	20
ACSR	21
Guy wire 1 x 7	16
Guy wire 1 x 19	16

## MODEL No. S-240A



**INCLUDED ITEMS**  
Cutter & Carry Bag

### SPECIFICATIONS

Output Force (kN)	76
Maximum Opening (mm)	24
Reservoir Capacity (cc)	70
Maximum Handle Load (N)	226
Size (mm)	425 (L)
Weight (kg)	4.0

### FEATURES

**Light weight portable hydraulic cutter cuts steel materials as well as cables up to 24mm OD. Single speed pump to reduce tool weight.**

The unit has a guillotine type cutting head for less jamming than shear type cutting heads. No set-up time is required and blades are easily replaceable. With a 180° swivel head and latch type head this allows easy cutting position and manoeuvrability.

### DETAILS

Cutting of piano wire is prohibited.

Cutting Capacity	
Material	mmOD
Wire rope 6 x7	18
Wire rope 6 x12	24
Wire rope 6 x 19	24
Rebar (400-500Mpa)	20
Rebar (650Mpa)	12.4
Reinforcing rod	16
Cu strands	24
Al strands	24
ACSR	24
Guy wire 1 x7	20
Guy wire 1 x 19	20