

MODEL No. S-320A







SPECIFICATIONS

Output Force (kN)	191
Maximum Opening (mm)	35
Reservoir Capacity (cc)	165
Maximum Handle Load (N)	276
Size (mm)	675(L)
Weight (kg)	9.3

FEATURES

Light weight portable hydraulic cutter cuts heavy steel materials up to 32 mm OD. Single speed pump to reduce tool weight.

Safety relief valve for overload protection. Guillotine type cutting for less jamming than shear type cutting. No set-up time required and blades are easily replaceable. 180° swivel and latch type head allows easy cutting position.

DETAILS

Cutting of piano wire is prohibited.

Cutting Capacity		
Material	mmOD	
Wire rope 6 x7	32	
Wire rope 6 x12	32	
Wire rope 6 x 19	32	
Soft steel bar	25	
Rebar (400-500Mpa)	25	
Rebar (650Mpa)	15.5	
Cu strands	32	
Al strands	32	
ACSR	32	
Guy wire 1 x7	32	
Guy wire 1 x 19	32	



SPECIFICATIONS

Output Force (kN)	58	
Maximum Opening (mm)	45	
Reservoir Capacity (cc)	120	
Maximum Handle Load (N)	196	
Pumping Cycles When No Load	17 times	
Two Stage Pumping		
No Relief Valve		
Size (mm)	578 (L)	
Weight (kg)	5.8	

FEATURES

Light weight portable hydraulic cutter cuts steel materials as well as cables up to 45mm OD and features two stage pumping for rapid blade advance.

A guillotine type cutting head for less jamming than shear type cutting. No set-up time is required and blades are easily replaceable. With a 180° swivel and lock pin type head, this allows for easy cutting position manoeuvrability.

DETAILS

Cutting of piano wire is prohibited.

Cutting Capacity		
Material	mmOD	
Wire rope 6 x7	22	
Wire rope 6 x12	25	
Wire rope 6 x 19	25	
Soft steel bar	20	
Rebar (400-500Mpa)	16	
Rebar (650Mpa)	12.4	
Cu strands	41	
Al strands	41	
ACSR	38	
Guy wire 1 x7	15	
Guy wire 1 x 19	20	