

**ELECTRIC CABLE PULLERS**



**Model No. 31466**  
**28.9 kN Rated**

**FEATURES**

- Pull heavy loads with minimal operator effort.
- Force Gauge included to constantly monitor the pull.
- Right-angle sheave allows the operator to stand out of the direct line of force.
- Audio alarm high force warning and circuit breaker shut off at maximum force for added safety.
- Tapered capstan and patented rope guidance system for better control of the rope when feeding onto the capstan.
- Runs off 230V/50/1 mains power.
- Patented.
- Direct gear drive with 1.1 KW motor.
- Supplied with clamping chains for pipe as standard.

**OPTIONAL EXTRAS**

- 35605 (6037) floor mount with 4 anchor's, heavy duty welded construction. Maximum Rated Capacity 28.9 kN, Weight 1.4kg.
- Pelican high force pulling rope recommended dia (19.1mm). Refer page 155 for details.



**Model No. 35605 (6037)**  
**Floor Mount**

Model No.	Pulling Force	Dimensions (LxWxH)	Weight (kg)
<b>31466</b>	Maximum 28.9 kN Continuous 20.0 kN	527x572x305	49

**Pulling Speed**

No Load 5 metre/minute

At 8.8 kN 3.4 metre/minute

At 17.9 kN 2.3 metre/minute

At 26.7 kN 1.8 metre/minute

**D WINCHES**

**www.specialisedforce.com.au**