

## **PORTABLE CAPSTAN WINCH PCW4000**

## Petrol Powered pulling winch with quick release automatic anti roll-back device.

Engine	All Positions, 4-Stroke, Honda GX50
Gearbox	Aluminum alloy gearbox. Heat-treated 3-stage helical and spur gears. Shaft mounted on ball bearings. Oil bath lubrication
Gear Ratio	200:1
Clutch	Type: Centrifugal Operate With: Quick release automatic anti-roll-back device
Brake	Anti-reversing roller clutch bearing
Dimesians (averall)	42 and 1/ 20 and 1/ 20 E and

Min Diameter: 10 mm Max. Diameter: 12 mm  Included Polyester sling 2 metres  Weight 12 kg	Liigille	All I Usidoris, 4-Sdoke, Horida UASU
Type: Centrifugal Operate With: Quick release automatic anti-roll-back device  Brake Anti-reversing roller clutch bearing  Dimesions (overall) 42 cm x 30 cm x 28.5 cm Ø 76 mm  Double braided polyester with low stretch PORTABLE WINCH CO. Length: Unlimited Min Diameter: 10 mm Max. Diameter: 12 mm  Included Polyester sling 2 metres Weight 12 kg	Gearbox	and spur gears. Shaft mounted on ball bearings. Oil
Clutch Operate With: Quick release automatic anti-roll-back device  Brake Anti-reversing roller clutch bearing  Dimesions (overall)  Drum  Ø 76 mm  Double braided polyester with low stretch PORTABLE WINCH CO. Length: Unlimited Min Diameter: 10 mm Max. Diameter: 12 mm  Included Polyester sling 2 metres  Weight  12 kg	Gear Ratio	200:1
Dimesions (overall)  Drum  Ø 76 mm  Double braided polyester with low stretch PORTABLE WINCH CO. Length: Unlimited Min Diameter: 10 mm Max. Diameter: 12 mm  Included Polyester sling 2 metres  Weight  12 kg	Clutch	Operate With: Quick release automatic anti-roll-back
Drum  Ø 76 mm  Double braided polyester with low stretch PORTABLE WINCH CO. Length: Unlimited Min Diameter: 10 mm Max. Diameter: 12 mm  Included Polyester sling 2 metres Weight  12 kg	Brake	Anti-reversing roller clutch bearing
Double braided polyester with low stretch PORTABLE WINCH CO. Length: Unlimited Min Diameter: 10 mm Max. Diameter: 12 mm  Included Polyester sling 2 metres Weight 12 kg	Dimesions (overall)	42 cm x 30 cm x 28.5 cm
Rope Recommended  Rope Recommended  Min Diameter: 10 mm Max. Diameter: 12 mm  Included  Polyester sling 2 metres  Weight  12 kg	Drum	Ø 76 mm
Included Polyester sling 2 metres Weight 12 kg	Rope Recommended	WINCH CO. Length: Unlimited Min Diameter: 10 mm
Weight 12 kg	To also de d	
		Polyester sling 2 metres
Power 1.4 kW	Weight	12 kg
10000	Power	1.4 kW



Winch





## PERFECT CONTROL WITH THE ANTI ROLLBACK MECHANISM

After nearly two years of work, Portable Winch Co. pulls off another master stroke in offering a winch that, while staying true to its predecessors by its power, its light weight and its reliability, stands out with a new feature that provides perfect control over the movement of a load: the quick release automatic anti rollback mechanism, also know as the ARM.

Also, since the PCW4000 is equipped with the Honda GX50 engine, a centrifugal clutch, a rope retention system and 1,000 kg of power in direct line, it becomes a formidable competitor on the market!

