



## PORTABLE CAPSTAN WINCH – PULLEYS



**PCA-1270**  
Open face corner block



**PCA-1271**  
Self-Blocking Pulley



**PCA-1272**  
Double Self-Blocking Pulley



**PCA-1273**  
Double Swing Side Pulley



**PCA-1274**  
Single Swing Side Pulley



**PCA-1275**  
Single Swing Side Pulley



**PCA-1292**  
Single Swing Side Pulley

Model No.	Feature	Material	WLL (kg)	Sheave Diam. (mm)	Length (cm)	Width (cm)	Height (cm)	Weight (kg)	Rope (mm) Min / Max	Cert.	Min Break Strength (kg)
<b>PCA-1270</b>	-	Steel	N/A	100	25	10	5.8	2.4	6 / 12	-	N/A
<b>PCA-1271</b>	Brake cam system allows the rope to go through freely in one direction and blocks it in the other direction.	Aluminium	N/A	62	23	10.5	8	0.7	10 / 12	CE	4079
<b>PCA-1272</b>	Two sheaves and a brake cam system - allow the rope to go through freely in one direction and block it in the other direction.		N/A	62	22	8.5	6.5	0.9	10 / 12	CE	4079
<b>PCA-1273</b>	Two lightweight 100 mm diameter deep groove aluminium sheaves.	Sides: Stainless steel.	4486	100	23	10.5	8	1.85	10 / 12	-	13775
<b>PCA-1274</b>	-	Sheave: Aluminium	2243	100	19.6	10.5	5.3	1.1	10 / 12	-	9185
<b>PCA-1275</b>	-	Aluminium	1632	76	15	8	3	0.6	10	-	6125
<b>PCA-1292</b>	-	Aluminium	N/A	63	13	9	4	0.3	6 / 12	CE	6000

## SPARE PARTS



**PCA-1110**  
Capstan Drum 57mm



**PCA-1100**  
Capstan Drum 85mm



**PCA-1120**  
Capstan Drum 76mm



**PCA-1130**  
Capstan Drum 108mm



**PCA-1151, PCA-1152**  
Spark Arrestor



**10-0044**  
Reversible Safety Lip

Model No.	Feature	Material	Diam. / Hole Diam. (mm)	Weight (kg)
<b>PCA-1100</b>	C/W rope guide and screws.	Aluminium	85 / 25.4	0.75
<b>PCA-1110</b>			57 / 25.4	0.35
<b>PCA-1120</b>			76 / 24.8	0.55
<b>PCA-1130</b>			108 / 24.8	0.75
<b>PCA-1151</b>	For Honda GXH-50 engine.		22 Ø	0.085
<b>PCA-1152</b>	For Gx160 engine		22 Ø	0.12
<b>10-0044</b>	For 57 mm and 85 mm drums. Prevents rope from jumping out of drum on all lifting winches: PCH1000, PCH2000 & PCT1800.		125	0.180