

CONTINUOUS FIBREGLASS RODS COILS





Quality- Australian Made.

Continuous coils of fibreglass rod, ideal for long distance rodding of ducts or conduits.

The rod includes a 1mm tracer wire in the centre and a 1.5mm layer of UV stabilised polyethylene sheathing for added protection and durability.

The set comes complete with a stand fitted (the 9mm & 11mm are supplied with wheels**) and a drag brake for holding the rod during operation, a threaded male fitting and removable eye on the outward end and a fixed eye on the inner end. The 9mm & 11mm also include a joining kit which consists of 2 joiners, 1 replacement eye, threaded end, glue and fitting instructions.

SIZES AND LENGTHS (All Sizes Include Trace Wire)

Model No.	Description	Length (m)	Dimensions (mm)	Wt (kg)	Replacement Rod
FRD5-40*	5mm Fibreglass Rodder	40	415x190x450	4.7	FRR5-40
FRD5-80*	5mm Fibreglass Rodder	80	415x190x450	5.1	FRR5-80
FRD7-75*	7mm Fibreglass Rodder	75	650x250x800	8.3	FRR7-75
FRD7-125*	7mm Fibreglass Rodder	125	650x250x800	13	FRR7-125
FRD7-150*	7mm Fibreglass Rodder	150	650x250x800	16	FRR7-150
FRD9-150**	9mm Fibreglass Rodder	150	800x450x1050	31	FRR9-150
FRD9-200**	9mm Fibreglass Rodder	200	800x450x1050	37	FRR9-200
FRD11-200**	11mm Fibreglass Rodder	200	1000x500x1250	55	FRR11-200
FRD11-250**	11mm Fibreglass Rodder	250	1000x500x1250	64	FRR11-250
FRD11-300**	11mm Fibreglass Rodder	300	1000x500x1250	73	FRR11-300





ACCESSORIES – Available for 5mm, 7mm, 9mm & 11mm rods







JOINER FIXING KITS

Repair Kit	Rod OD	Each Kit Contains		
Model No.	(mm)	QTY	Description	
JK-05	5	2	Joiner Sleeves	
JK-07	7	1	Male End Fitting	
JK-09*	9	1	Female End Fitting with Eye	
	11	1	Fitting Instruction	
JK-11*		2	Epoxy Glue, Mixing Sticks & Sheets, Sandpaper Strips (Model No. FRDG)	

^{*}Joiner Fixing Kit Supplied as standard with 9mm $\&\ 11\text{mm}$ Rodders.



Avoid contact with skin and eyes. For skin, Wash affected area with soap and water. Do not take internally. If taker internally seek medical attention immediately. If in Contact with eyes, flush, with plenty of water. Use with adequate ventilation.

Ventilation.

How to service a broken rod with an internal tracer wire. Use the appropriate fittings for the diameter of the rod. Cutoff, squarely, the 2 broken ends with fine toothed hacksaw. Mark rod @ 40mm from end for 8mm rod. @ 34mm from end for 6mm rod. & 28mm for 4mm rod. Carefully cut poly cover circumferentially @ mark and remove poly cover.



POLYCARBONATE HAND RODS – Available 22mm Diameter x 3m Lengths



All Accessories available as with the Fibreglass Rodders.

Model No.	Description
PHR-223M	22mmOD Polycarbonate Hand Rods, 3m L, 0.9kg each. Fitted with M&F Brass End Couplers
PHR-22C	Plastic Hand Crank Rod
PHR-22F	Hand Rod Female Fitting
PHR-22FE	Female End with Eye
PHR-22M PHR-22ME	Hand Rod Male Fitting Male End with Eye
PHR-22FL	Bullet Leader Male
PHR-22ML	Bullet Leader Male
PHR-22GH	Grappling Hook Male Ends







Model No. **PHR-22C**