

# DP 217 ATEX

Square drive	3/4"
Bolt range	M14-M24
Max torque	1700 Nm - 1260 ft-lb
Working torque	350-910 Nm - 240-680 ft-lb
Free speed	5400 rpm
Impacts number	1000/min
Working pressure	6,3 bar - 91 psi
Air inlet	1/2" BSP
Inner hose diameter	13 mm - 0.512 in
Length	221 mm - 8.7 in
Side to center	48 mm - 1.9 in
Vibration level - triaxial	9,4 m/s <sup>2</sup>
Sound pressure level	104 dB(A)



## INCLUDED IN THE BOX



The package contains: lifting eye bolt, handle (in compliance with the CE UNI EN ISO 11148-6 norm), oil for impact wrench motors, operating and maintenance manual, after-sales suggestions.

## MAIN FEATURES

-  Hammer mechanism: 3-jaw
-  Anvil type: with ring, with hole
-  Air exhaust direction: through the handle
-  Hammer mechanism lubrication: grease

## BEST FOR

-  Mine and oil field
-  Construction site and shipyard
-  Industrial assembly
-  Offshore platforms



Hammer mechanism: 3-jaw

Certified paint



Air exhaust through the handle  
 • less noise  
 • no harmful dust

Air inlet with phosphate manganese coating treatment

AVAILABLE MODELS	PRODUCT CODE	WEIGHT	OUTER MATERIAL
 I M2 IIB T6 II 2 GD IIB T6	A.07.11.0002	7,5 kg 1.5 lbs	Zama
 II 2 GD IIB T6 II 3 G IIB T6	A.07.11.0003	6,1 kg 13.4 lbs	Aluminium