



DP 246 ATEX

Product code	A.07.51.0001
Square drive	1"
Bolt range	M18-M39
Max torque	2800 Nm -2070 ft-lb
Working torque	600-1400 Nm - 440-1020 ft-lb
Weight	8,24 kg - 18.2 lbs
Free speed	4200 rpm
Impacts number	750/min
Working pressure	6,3 bar - 91 psi
Air inlet	1/2" BSP
Inner hose diameter	13 mm - 0.512 in
Length	282 mm - 11.1 in
Side to center	50 mm - 1.97 in
Vibration level - triaxial	4,079 m/s ³
Sound pressure level	94 dB(A)







INCLUDED IN THE BOX



The package contains: handle (in compliance with the CE UNI EN ISO 11148-6 norm), oil for pneumatic motors, operating and maintenance manual, after-sales suggestions.

MAIN FEATURES

-  Hammer mechanism: pin-clutch
-  Anvil type: with ring, with hole
-  Air exhaust direction: through the handle
-  Hammer mechanism lubrication: oil

BEST FOR

-  Mine and oil field
-  Construction site and shipyard
-  Industrial assembly
-  Offshore platforms

Pin-Clutch hammer mechanism with oil bath lubrication system
Long-lasting hammer mechanism life

Certified paint



Air exhaust through the handle

- less noise
- no harmful dust

Air inlet with phosphate manganese coating treatment

 II 2 GD IIBT6
II 3 G IIBT6



specialisedforce.com.au