

# RED DEVIL SL ATEX

Product code	A.07.01.0001
Square drive	1/2"
Bolt range	M10-M24
Max torque	800 Nm - 590ft-lb
Working torque	80-600 Nm - 60-450 ft-lb
Weight	2,40 kg - 5.30 lbs
Free speed	12000 rpm
Impacts number	2000/min
Working pressure	6,5 bar - 94 psi
Air inlet	1/4" NPT
Inner hose diameter	13 mm - 0.512 in
Length	192,6 mm - 7.58 in
Side to center	40 mm - 1.57 in
Vibration level - triaxial	9,1 m/s <sup>2</sup>
Sound pressure level	97 dB(A)







## INCLUDED IN THE BOX



The package contains: oil for impact wrench motors, operating and maintenance manual, after-sales suggestions.

## MAIN FEATURES

-  Hammer mechanism: twin hammer
-  Anvil type: with ring, without hole
-  Air exhaust direction: sides exhaust
-  Hammer mechanism lubrication: grease

## BEST FOR

-  Mine and oil field
-  Construction site and shipyard
-  Industrial assembly
-  Offshore platforms



Twin hammer mechanism

 II 2 GD IIBT6  
II 3 G IIBT6

Certified paint

Air inlet with phosphate manganese coating treatment



[specialisedforce.com.au](http://specialisedforce.com.au)