


## www.specialisedforce.com.au







## Description:

Powerful: 6.5 tonne, 10 tonne and 15 tonne capacity.

Proven: Thousands in use around the world.

Well Engineered: Servicing and repairs easily undertaken.

Safe: Relief valve prevents overloading.

Compact and Lightweight:Ideal portable tool.

Versatile: Operates in any orientation, totally enclosed and suitable for use in dusty conditions.

Easy to Operate: Lift/lowering controlled easily by operating lever.

| Product Code           | 8104H       |            | 1105002     |            | 1105003     |            |
|------------------------|-------------|------------|-------------|------------|-------------|------------|
| Capacity               | 6.5 tonne   |            | 10 tonne    |            | 15 tonne    |            |
| Oil Capacity           | 0.10 Litres | 0.17 Pints | 0.13 Litres | 0.23 Pints | 0.27 Litres | 0.48 Pints |
| Jack Weight            | 3.6 kg      | 81bs       | 6.3kg       | 13.9 lbs   | 10.0 kg     | 22 lbs     |
| Dimensions             | mm          | ins        | mm          | ins        | mm          | ins        |
| A - Base Width         | 76          | 2.99       | 76          | 3          | 92          | 3.62       |
| B - Base Depth         | 158         | 6.22       | 171         | 6.73       | 197         | 7.75       |
| C - Closed Height      | 140         | 5.51       | 182         | 7.17       | 230         | 9.06       |
| D - Stroke             | 75          | 2.95       | 115         | 4.5        | 152         | 5.98       |
| E - Max Depth          | 190         | 7.48       | 207         | 8.15       | 236         | 9.29       |
| F - Centre Ram to Face | 33.3        | 1.31       | 40          | 1.57       | 48          | 1.89       |
| Ram Diameter           | 30          | 1.18       | 38          | 1.5        | 47.5        | 1.87       |
| Service Kit Number     | 995052      |            | 995053      |            | 995054      |            |