



FEEDING SHEAVES & GUIDES

IFS SERIES IN-LINE BELL MOUTH

Placed inside conduit with "bell mouth" to aid with laying cables, also has spreader bolt to lock tight into conduit. Chrome zinc plated finish.

FS SERIES LOCKABLE FEEDING SHEAVES

Lockable feeding sheave with roller (115/140mmOD) to aid the entrance and exiting of cables through conduits.

FS-*-4R LOCKABLE MULTIPLE ROLLER GUIDE**

The quad roller is a multi-directional roller guide. This sheave has the added benefit of a hinged top roller for removal of cable and roller guide from conduit. Chrome zinc plated finish.

FS-*-4A90 LOCKABLE FEEDING SHEAVE WITH 4 ROLLERS IN 90° RADIUS**

Lockable angled guiding rollers for inside manholes are set at 90° with a radius of 450mm. Suitable for directional changes within a manhole. The support frame rests against the wall offering added strength should the pull require it. Zinc plated finish on all with lockable with tension bolt.



Image	Model No. *	Dimensions (mm)	Conduit Nom. OD (mm)	Approx Equip OD (mm)	Weight (kg)	
 <p>IFS Series</p>	IFS-050E	255 X 120 X 115	50	42	1.60	
	IFS-050T	255 X 130 X 115	50	48	1.60	
	IFS-063E	255 X 140 X 115	63	48	1.60	
	IFS-063T	250 X 155 X 110	63	60	1.70	
	IFS-080	250 X 200 X 140	80	74	1.80	
	IFS-100	250 X 220 X 155	100	98	2.80	
	IFS-125	250 x 240 x 165	125	118	3.20	
	IFS-150	250 x 260 x 175	150	138	4.40	
	 <p>FS Series</p>	FS-050E	370 X 160 X 180	50	38	2.90
		FS-050T	380 X 160 X 180	50	48	3.30
FS-063E		380 X 160 X 180	63	48	3.30	
FS-063T		380 X 160 X 180	63	60	3.30	
FS-080		370 X 170 X 200	80	74	3.50	
FS-100		390 X 190 X 210	100	98	5.60	
FS-125		390 X 200 X 220	125	118	6.10	
FS-150		400 X 230 X 230	150	138	6.40	
FS-200		460 X 280 X 320	200	190	13.90	
 <p>FS-***-4R Series</p>		FS-080-4R	360 x 200 x 170	80	74	5.20
	FS-100-4R	380 x 220 x 180	100	98	6.50	
	FS-125-4R	390 X 230 X 260	125	118	7.00	
	FS-150-4R	390 X 260 X 280	150	138	7.90	
	FS080-4A90	900 X 620 X 260	80	74	12.20	
	FS100-4A90	900 X 620 X 260	100	98	15.00	
	FS125-4A90	900 X 620 X 260	125	118	15.00	
	FS150-4A90	900 X 620 X 260	150	138	15.00	
	FS200-4A90	900 X 620 X 260	200	190	23.80	

* "T" for Telecommunications Conduit or "E" for Electrical Conduit